

SURVEY No. 3863.

The Daney Tunnel, 7 ft. high and 5 ft wide, the center of the entrance to which bears from Cor. No. 1 N. 44°55'E. 482.30 ft. and running thence S. 83°02'W. 1032.3 ft. to point No. 1; thence S. 47°26'W. 77.70 ft. to point No. 2 above mentioned, and was run to drain this claim.

An open cut, the west end center of which bears from Cor. No. 1 N. 81°45'W. 798 ft. and extending S. 63°10' E. 230 ft., average width 20 ft., average depth 15 ft.

An open cut, the east end center of which bears from Cor. No. 1, N. 81°15'W. 811 ft. and extending thence N. 56°10' W. 90 ft., average width 18 ft., average depth 10 ft.

The Old Daney Shaft, 15 ft. long by 5 ft. wide, the S. E. corner of which bears from Cor. No. 1 N. 73°44'W. 728.50 ft. This shaft is badly caved but was originally sunk below the tunnel level. There are no contiguous claims.

Instrument.

This survey was made with a C. L. Berger and Sons Light Mining and Reconnaissance Transit No. 4. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with 100 ft. and 500 ft. steel tapes.

Report.

The improvements named "other improvements" were made by the "Old" Daney Mining Company many years prior to the location of the claim by the grantors of claimant, and therefore cannot be counted as development work by present claimant. The ground was relocated several times after being abandoned by the Daney Company and before being located by grantors of present claimant.

The lode line of this claim was run direct upon the ground and the several corners established by means of offsets from the lode line. All tie lines were run direct upon the ground.

The N. E. Cor. of Sec. 28 T. 16 N., R. 21 E. M.D.B. and M. is a stone improperly chiseled with three notches on the