Form 9600—19
(May 1978)
(formerly 9180—21)

Mineral Survey No. 4971

	FEET	
		All lines and connections of this survey were run by direct methods except as noted. The magnetic declination observed at each cor. gave a uniform value of 17°30' E.
		HOMRF #1 MILL SITE MILLSITE At Cor. No. 1 of the HOMRF #1 mill site millsite. Set an iron post, 24 ins. long, 2 ins. diam., 14 ins. in the ground, with a brass cap mkd. HOMRF#1-Cor-1-MS4971; from which The SE cor. of sec. 6, T. 16 N., R. 21 E., Mt. Diablo Mer., bears S. 76°38'42" E., 2,052.45 ft. dist., monumented with an iron post, 1/2 ins. diam., 10 ins. above ground, firmly set in a md. of stone, with 2 ins. diam. steel washer mkd. 5-6-7-8. No evidence of original cor. found. The NW cor. of sec. 6, T. 16 N., R. 21 E., Mt. Diablo Mer., bears N. 35°08'00" W., 5,927.34 ft. dist., monumented with an iron post, 2½ ins. diam., 20 ins. above ground, surrounded by a stone md., with a brass cap mkd. S1-S6-S31-S36-T16N-T17N-R20E-R21E-1947-U.S. General Land Office Survey.
		Thence N. 89°59'49" W.
	35.	Center of wood drain, 6 ins. deep x 12 ins. wide, course S. 76° E.
	265.60	Cor. No. 2. Set an iron post, 24 ins. long, 2 ins. diam., 21 ins. in the ground, with a brass cap mkd. HOMRF#1-Cor-2-MS4971. No local bearing objects or bearing trees available.
		Thence N. 0°00'11" E.
	200.00	Cor. No. 3. Set an iron post, 24 ins. long, 2 ins. diam., 18 ins. in the ground, with a brass cap mkd. HOMRF#1-Cor-3-MS4971. No local bearing objects or bearing trees available.
		Thence N. 89°59'49" W.
	33.	Enter course material stock pile, edge bears N. 44° W. and S. 44° E.

(This form bound on left side)