UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF SECTIONS 14, 15, 16, 17, 23, AND 26

TOWNSHIP 20 NORTH, RANGE 30 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Kelly R. Totten, Cadastral Surveyor

Under Special Instructions dated February 20, 2025,

and approved February 20, 2025,

which provided for the surveys included under Group No. 1023,

and Assignment Instructions dated February 20, 2025.

Survey commenced February 26, 2025

Survey completed September 1, 2026

INDEX DIAGRAM

TOWNSHIP 20 NORTH, RANGE 30 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	*5*	*4*	*3*	*2*	*1*
7	*8* 29	*9* 22	*10* 16	*11* 10	*12*
18	27 *17* 27	21 *16* 20	15 *15* 14	9 *14* 8	4 *13*
19	26 *20* 26	19 *21* 19	13 *22* 13	7 *23* 7	3 *24*
30 24	25 *29* 23	18 *28* 18	12 *27* 11	5 *26*	2 *25*
31	22 *32*	16 *33*	10 *34*	*35*	*36*

Subdivision of Section 14.....pp 29 - 30
Subdivision of Section 15..... p 30
Subdivision of Section 16.....p 30
Subdivision of Section 17.....pp 30 - 31
Subdivision of Section 23..... p 31
Subdivision of Section 26.....pp 31 - 32

TOWNSHIP 20 NORTH, RANGE 30 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 14, 15, 16, 17, 23, and 26, Township 20 North, Range 30 East, Mount Diablo Meridian, Nevada. 1865 - The north boundary (Fourth Standard Parallel North), was surveyed by U.S. Deputy Surveyor W. Epler, under Contract I. 1868 - The south, east, and west boundaries, and the subdivisional lines were surveyed by U.S. Deputy Surveyor E.B. Monroe, under Contract Nos. 10 and 16. 1903-04 - Portions of the township were resurveyed by A.H. Thomas for the United States Geological Survey; the unrecorded field notes are on file with the Truckee-Carson Irrigation District. 1978-79 - A portion of the south boundary and a portion of the subdivisional lines were dependently resurveyed and sections 33, 34, and 35 were subdivided by Cadastral Surveyors N.R. Forsyth, D.E. Provost, and R.E. Williams under Group No. 568. Other surveys remote to this area are not included. The dependent resurvey of a portion of the north boundary of T. 19 N., R. 30 E., and a portion of the east boundary of T. 20 N., R. 29 E., was executed concurrently under Group Nos. 1019 and 1022 respectively. Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the position of the original corners and other calls of the original field note record. The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey. The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1023, dated February 20, 2025. Measurements were made with Trimble R10-2 and R12i Global Navigation Satellite System (GNSS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes. The NAD 83(2011)(EPOCH:2010.0000) geographic position, of the following corners was determined from Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS); DH4796 TUNG TUNG_BRGN_NV1996 CORS MON, DR8089 P129 DEADCOWPT_NV2007 CORS GRP, DR8187 P069 INDIANPEAKNV2006 CORS GRP,

TOWNSHIP 20 NORTH, RANGE 30 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

AI8816 UPSA UPSA_BRGN_NV1997 ECCREF DIMPLE,
DR8187 P069 INDIANPEAKNV2006 CORS GRP,
and carried forward by RTK observations.

The corner of sections 25, 26, 35, and 36, is as follows:

Latitude: 39°33'46.833" N. Longitude: 118°34'29.266" W.

The corner of sections 7, 8, 17, and 18, is as follows:

Latitude: 39°36'23.596" N. Longitude: 118°39'02.264" W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.B. Monroe in 1868 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyors N.R. Forsyth, D.E. Provost, and R.E. Williams in 1978-79

Beginning at the cor. of secs. 25, 26, 35, and 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with an aluminum cap mkd.

T20N R30E

S26	S25
S35	S36

1978

with a steel fence post lying loose alongside.

N. 0°06'40" W., bet. secs. 25 and 26.

40.104 The 1/4 sec. cor. of secs. 25 and 26, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 12x6x5 ins. (Thomas Record: 14x8x6 ins.), firmly set, 3 ins. below the surface of the ground, mkd. 1/4 on the W. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T20N R30E 1/4 S26 | S25 2025 Bury mkd. stone alongside stainless steel post.
	N. 0°11'00" W., beginning new measurement.
36.90	Canal, 50 lks. wide, bears NE. and SW.
40.112	The cor. of secs. 23, 24, 25, and 26, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 14x11x3 ins. (Thomas Record: 16x8x5 ins.), lying loose, mkd. with 1 groove on one face and 2 grooves on another face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, with a wood post, 3x3 ins., 4 ft. long, lying loose alongside, no marks visible, and the decayed remains of a wood post, 2 1/2 ins. dia., 1 1/2 ft. long, lying loose alongside, no marks visible. The stone is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S23 | S24 S26 | S25 2025 Bury mkd. stone and deposit wood post and decayed remains of wood post alongside stainless steel post.
	N. 0°01'40" W., bet. secs. 23 and 24.
8.40	Overgrown unimproved dirt road, bears S. 55° E. and N. 55° W.
40.110	The 1/4 sec. cor. of secs. 23 and 24, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 11x8x5 ins. (Thomas Record: 14x6x4 ins.), firmly set, 1 in. below the surface of the ground, mkd. 1/4 on the W. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner. At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E 1/4 S23 | S24 2025 Bury mkd. stone alongside stainless steel post.
	N. 0°07'30" W., beginning new measurement.
40.130	The cor. of secs. 13, 14, 23, and 24, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 12x7x5 ins. (Thomas Record: 16x8x6 ins.), firmly set, projecting 5 ins. above the ground, mkd. with 1 groove on the E. face and 3 grooves on the S. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S14 | S13 S23 | S24 2025 Bury mkd. stone alongside stainless steel post.
	N. 0°02'50" W., bet. secs. 13 and 14.
40.120	The 1/4 sec. cor. of secs. 13 and 14, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 11x8x5 ins. (Thomas Record: 14x8x6 ins.), lying loose, mkd. 1/4 on a face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T20N R30E 1/4 S14 | S13 2025 Bury mkd. stone alongside stainless steel post.
	N. 0°15'00" W., beginning new measurement.
6.70	Shallow canal, 40 lks. wide, bears E. and NW.
40.124	The cor. of secs. 11, 12, 13, and 14, perpetuated by A.H. Thomas, in 1904, for the USGS, and further perpetuated by person(s) unknown, monumented with a rebar, 5/8 ins. diam., 24 ins. long, firmly set, projecting 5 ins. above the ground, no record found, with a basalt stone 12x6x6 ins. (Thomas Record: 16x8x6 ins.), with 1 groove on one face and 4 grooves on another face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, lying loose alongside, and with a steel fence post, firmly set, projecting 4 ft., alongside. The rebar is accepted as a careful and faithful perpetuation of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S11 | S12 S14 | S13 2025 Insert rebar inside and bury mkd. stone alongside stainless steel post. Reset the steel fence post alongside stainless steel post.
	From the cor. of secs. 26, 27, 34, and 35, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 20 N., R. 30 E., executed under Group No. 568, with a basalt stone, 9x6x4 ins., mkd. with 2 grooves on one face and 1 groove on another face, lying loose alongside. N. 0°04'50" E., bet. secs. 26 and 27.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.036	The 1/4 sec. cor. of secs. 26 and 27, perpetuated by A.H. Thomas, in 1904, for the USGS, and further perpetuated by person(s) unknown, monumented with a rebar, 5/8 ins. diam., 30 ins. long, firmly set, projecting 14 ins. above the ground, no record found, with a basalt stone, 13x12x5 ins. (Thomas Record: 12x6x4 ins.), mkd. 1/4 on a face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, lying loose alongside and is accepted as a careful and faithful perpetuation of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E 1/4 S27 | S26 2025 Insert rebar inside and bury mkd. stone alongside stainless steel post. --- N. 0°00'20" E., beginning new measurement.
40.124	The cor. of secs. 22, 23, 26, and 27, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 11x11x3 ins. (Thomas Record: 16x8x6 ins.), firmly set, 6 ins. below the surface of the ground, mkd. with 2 grooves on the S. face and 2 grooves on the E. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and with a decayed wood post, 4x3 ins., 24 ins. long, no marks visible, lying loose alongside, and is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S22 | S23 --- S27 | S26 2025 Bury mkd. stone and deposit wood post alongside stainless steel post. ---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the cor. of secs. 23, 24, 25, and 26.
	N. 89°56'20" W., bet. secs. 23 and 26.
40.754	The 1/4 sec. cor. of secs. 23 and 26, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 10x10x5 ins. (Thomas Record: 16x9x6 ins.), lying loose, mkd. 1/4 on a face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S23 1/4 —— S26 2025
	Bury mkd. stone alongside stainless steel post.
	N. 89°55'20" W., beginning new measurement.
40.600	The cor. of secs. 22, 23, 26, and 27.
	N. 0°00'10" W., bet. secs. 22 and 23.
33.65	Overgrown unimproved dirt road, bears N. 70° E. and S. 70° W.
40.088	The 1/4 sec. cor. of secs. 22 and 23, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 11x9x6 ins. (Thomas Record: 14x6x6 ins.), firmly set, 6 ins. below the surface of the ground, mkd. 1/4 on the W. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T20N R30E 1/4 S22 | S23 2025 Bury mkd. stone alongside stainless steel post. N. 0°01'40" E., beginning new measurement.
40.100	The cor. of secs. 14, 15, 22, and 23, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 12x7x6 ins. (Thomas Record: 16x8x6 ins.), firmly set, 12 ins. below the surface of the ground, mkd. with 2 grooves on the E. face and 3 grooves on the S. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S15 | S14 S22 | S23 2025 Bury mkd. stone alongside stainless steel post.
	From the cor. of secs. 13, 14, 23, and 24. N. 89°57'00" W., bet. secs. 14 and 23.
40.788	The 1/4 sec. cor. of secs. 14 and 23, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 14x9x5 ins. (Thomas Record: 12x6x5 ins.), firmly set, projecting 4 ins. above the ground, mkd. 1/4 on the N. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T20N R30E S14 1/4 —— S23 2025
	Bury mkd. stone alongside stainless steel post.
	N. 89°59'10" W., beginning new measurement.
40.424	The cor. of secs. 14, 15, 22, and 23.
	N. 0°01'10" E., bet. secs. 14 and 15.
40.304	The 1/4 sec. cor. of secs. 14 and 15, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 12x8x5 ins. (Thomas Record: 14x7x5 ins.), firmly set, projecting 4 ins. above the ground, mkd. 1/4 on the W. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R30E 1/4 S15 | S14 2025
	Bury mkd. stone alongside stainless steel post.
	N. 0°03'00" E., beginning new measurement.
37.00	Canal, 60 lks. wide, bears E. and SW.
40.318	The cor. of secs. 10, 11, 14, and 15, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 11x8x4 ins. (Thomas Record: 16x8x8 ins.), firmly set, projecting 8 ins. above the ground, mkd. with 2 grooves on the E. face and 4 grooves on the S. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner.
	At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S10 | S11 S15 | S14 2025 Bury mkd. stone alongside stainless steel post.
	From the cor. of secs. 11, 12, 13, and 14. N. 89°42'00" W., bet. secs. 11 and 14.
40.418	The 1/4 sec. cor. of secs. 11 and 14, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 11x7x6 ins. (Thomas Record: 14x8x6 ins.), firmly set, projecting 4 ins. above the ground, mkd. 1/4 on the N. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S11 1/4 S14 2025 Bury mkd. stone alongside stainless steel post.
	N. 89°42'00" W., beginning new measurement.
40.524	The cor. of secs. 10, 11, 14, and 15.
	From the 1/4 sec. cor. of secs. 33 and 34, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, 4 ins. below the surface of the ground, with an aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 20 N., R. 30 E., executed under Group No. 568. Corner is located in a barbed wire fence, bears E. and W., with a barbed wire fence extending S., and 52 lks. N. of a three wire overhead power transmission line, bears E. and W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 0°01'30" E., bet. secs. 33 and 34.
40.118	The cor. of secs. 27, 28, 33, and 34, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 15x12x4 ins. (Thomas Record: 14x12x4 ins.), lying loose, mkd. with 3 grooves on a face and 1 notch on an edge, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and with a steel fence post 5 ft. long, and a wood post, 3x3 ins., 4 ft. long, lying loose alongside, and is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S28 | S27 S33 | S34 2025 Bury mkd. stone and deposit the wood post and steel fence post alongside stainless steel post. From this corner, a wood post, 3x3 ins., 4 ft. long, lying loose, no marks visible, bears SE., 15 lks. dist., and is not utilized during the course of this survey.
	From the cor. of secs. 26, 27, 34, and 35. S. 89°30'40" W., bet. secs. 27 and 34.
40.334	The 1/4 sec. cor. of secs. 27 and 34, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, 2 ins. below the surface of the ground, with an aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 20 N., R. 30 E., executed under Group No. 568, with a steel fence post alongside.
	S. 89°33'40" W., beginning new measurement.
40.352	The cor. of secs. 27, 28, 33, and 34.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 0°08'10" E., bet. secs. 27 and 28.
40.698	The 1/4 sec. cor. of secs. 27 and 28, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 14x10x5 ins. (Thomas Record: 12x6x4 ins.), lying loose, mkd. 1/4 on a face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E 1/4 S28 | S27 2025 Bury mkd. stone alongside stainless steel post. From this corner, a wood post, 2x2 ins., 2 ft. long, lying loose, no marks visible, bears NE., 30 lks. dist., and is not utilized during the course of this survey.
	N. 0°05'30" E., beginning new measurement.
40.658	The cor. of secs. 21, 22, 27, and 28, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 13x11x5 ins. (Thomas Record: 12x10x4 ins.), lying loose, mkd. with 3 grooves on a face and 2 notches on an edge, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S21 | S22 S28 | S27 2025 Bury mkd. stone alongside stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the cor. of secs. 22, 23, 26, and 27.
	N. 89°37'40" W., bet. secs. 22 and 27.
40.322	The 1/4 sec. cor. of secs. 22 and 27, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 13x10x3 ins. (Thomas Record: 14x8x6 ins.), lying loose, mkd. 1/4 on a face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S22 1/4 —— S27 2025
	Bury mkd. stone alongside stainless steel post.
	N. 89°35'50" W., beginning new measurement.
40.244	The cor. of secs. 21, 22, 27, and 28.
	N. 0°04'20" E., bet. secs. 21 and 22.
14.80	Overgrown unimproved dirt road, bears N. 75° E. and S. 75° W.
40.136	The 1/4 sec. cor. of secs. 21 and 22, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 14x7x6 ins. (Thomas Record: 14x10x4 ins.), lying loose, mkd. 1/4 on a face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E 1/4 S21 | S22 2025
	Bury mkd. stone alongside stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 0°03'20" E., beginning new measurement.
40.022	The cor. of secs. 15, 16, 21, and 22, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 17x10x4 ins. (Thomas Record: 14x8x6 ins.), lying loose, mkd. with 3 grooves on a face and 3 grooves on another face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S16 | S15 S21 | S22 2025 Bury mkd. stone alongside stainless steel post.
	From the cor. of secs. 14, 15, 22, and 23. N. 89°36'30" W., bet. secs. 15 and 22.
40.228	The 1/4 sec. cor. of secs. 15 and 22, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 12x6x4 ins. (Thomas Record: 14x8x6 ins.), firmly set, 12 ins. below the surface of the ground, mkd. 1/4 on the N. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S15 1/4 —— S22 2025 Bury mkd. stone alongside stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 89°39'40" W., beginning new measurement.
40.248	The cor. of secs. 15, 16, 21, and 22.
	N. 0°03'40" W., bet. secs. 15 and 16.
40.178	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E 1/4 S16 | S15 2025 From this point, the decayed remains of a wood post, 3x3 ins., 14 ins. long, no marks visible, lying loose, bears S., 36 lks. dist., and is not utilized during the course of this survey.
80.356	Point for the cor. of secs. of 9, 10, 15, and 16, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S 9 | S10 S16 | S15 2025 Point is located 30 lks. S. of a graded dirt road, 35 lks. wide, bears N. 70° E. and S. 70° W. From this point, the 1/4 sec. cor. of secs. 9 and 10, bears N. 0°18'50" E., 40.179 chs. dist., reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 11x10x4 ins. (Thomas Record: 12x8x4 ins.), lying loose, mkd. 1/4 on a face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T20N R30E 1/4 S 9|S10 2025 Bury mkd. stone alongside stainless steel post. Corner is located 3.70 chs. S. of overgrown dirt road, bears E. and W.
	From the cor. of secs. 10, 11, 14, and 15. N. 89°49'30" W., bet. secs. 10 and 15.
40.296	Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; a basalt stone, 12x8x6 ins. (Thomas record: 14x8x6 ins.), set by A.H. Thomas, in 1904, for the USGS, was found in a disturbed position, lying loose on the root ball of a cottonwood stump, 36 ins. diam., mkd. 1/4 on a face, bears N. 52°53'50" E., 4.064 chs. dist., original position indeterminate. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S10 1/4 —— S15 2025 Add the marks AM to mkd. stone and bury alongside stainless steel post.
80.592	The cor. of secs. 9, 10, 15, and 16.
	From the 1/4 sec. cor. of secs. 32 and 33, determined at a wood fence corner post, 9x7 ins., firmly set, projecting 7 ft. above the ground, with barbed wire fences extending E. and S. The fence corner correlates well with the 1978-79 dependent resurvey and is substantiated by an aluminum post, 30 ins. long, 2 1/2 ins. diam., found lying loose and in a disturbed position, original location indeterminate, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 20 N., R. 30 E., executed under Group No. 568. The fence corner is accepted as the best available evidence of the position of the original corner. from which

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 8°49' E., 45.5 lks. dist., with brass cap mkd. RM T20N R30E 30.0 FT. TO COR S 33 2025 and an arrow pointing to the corner.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 82°04' W., 45.5 lks. dist., with brass cap mkd. RM T20N R30E 30.0 FT. TO COR S 32 2025 and an arrow pointing to the corner.

Bury the 1979 aluminum post inverted alongside the fence corner post.

Corner is located 41 lks. N. of three wire overhead power transmission line, bears E. and W.

N. 0°05'00" E., bet. secs. 32 and 33.

39.958 The cor. of secs. 28, 29, 32, and 33, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 14x8x5 ins. (Thomas Record: 14x8x6 ins.), lying loose, mkd. with 4 grooves on a face and 1 groove on another face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and with a steel fence post, 5 ft. long, lying loose alongside, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T20N R30E

S29	S28
S32	S33

2025

Bury mkd. stone and reset steel fence post alongside stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the cor. of secs. 27, 28, 33, and 34.
	S. 89°29'30" W., bet. secs. 28 and 33.
40.468	The 1/4 sec. cor. of secs. 28 and 33, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with an aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 20 N., R. 30 E., executed under Group No. 568, with a basalt stone, 8x6x3 ins., firmly set, projecting 6 ins. above the ground, mkd. 1/4 on the W. face, alongside the aluminum post.
	S. 89°05'10" W., beginning new measurement.
40.162	The cor. of secs. 28, 29, 32, and 33.
	N. 0°11'10" W., bet. secs. 28 and 29.
40.892	The 1/4 sec. cor. of secs. 28 and 29, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 17x11x4 ins. (Thomas Record: 12x6x4 ins.), firmly set, projecting 9 ins. above the ground, mkd. 1/4 on the W. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E 1/4 S29|S28 2025 Bury mkd. stone alongside stainless steel post.
	N. 0°02'40" W., beginning new measurement.
19.65	Overgrown unimproved dirt road, bears N. 55° E. and S. 55° W.
40.800	Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance, based on the measurements from the unrecorded 1904 field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T20N R30E S20 | S21 S29 | S28 2025
	From the cor. of secs. 21, 22, 27, and 28.
	S. 89°31'00" W., bet. secs. 21 and 28.
29.70	Unimproved dirt road, 12 lks. wide, bears S. 35° E. and N. 25° W.
40.434	The 1/4 sec. cor. of secs. 21 and 28, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 10x9x5 ins. (Thomas Record: 12x6x6 ins.), lying loose, mkd. 1/4 on a face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R30E S21 1/4 S28 2025
	Bury mkd. stone alongside stainless steel post.
	S. 89°32'50" W., beginning new measurement.
40.498	The cor. of secs. 20, 21, 28, and 29.
	N. 0°01'50" W., bet. secs. 20 and 21.
40.098	Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T20N R30E 1/4 S20 | S21 2025
80.196	The cor. of secs. 16, 17, 20, and 21, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 12x12x5 ins. (Thomas Record: 16x8x6 ins.), lying loose, mkd. with 4 grooves on a face and 3 grooves on another face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S17 | S16 --- S20 | S21 2025 Bury mkd. stone alongside stainless steel post.
	From the cor. of secs. 15, 16, 21, and 22. S. 89°34'00" W., bet. secs. 16 and 21.
40.490	The 1/4 sec. cor. of secs. 16 and 21, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 11x9x5 ins. (Thomas Record: 14x8x6 ins.), firmly set, 24 ins. below the surface of the ground, mkd. 1/4 on the N. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T20N R30E S16 1/4 —— S21 2025
	Bury mkd. stone alongside stainless steel post.
	From this corner, USGS benchmark "INDIAN" monumented with concrete post, 8 ins. diam., projecting 22 ins. above the ground, with a standard disk mkd. INDIAN 1950, bears N. 0°28'20" W., 29.823 chs. dist.
	S. 89°33'10" W., beginning new measurement.
40.558	The cor. of secs. 16, 17, 20, and 21.
	N. 0°00'20" E., bet. secs. 16 and 17.
40.130	The 1/4 sec. cor. of secs. 16 and 17, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 15x7x3 ins. (Thomas Record: 14x6x6 ins.), lying loose, mkd. 1/4 on a face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R30E 1/4 S17|S16 2025
	Bury mkd. stone alongside stainless steel post.
	N. 0°10'00" W., beginning new measurement.
17.45	Canal, 25 lks. wide, bears E. and W.
30.35	Graded dirt road, 45 lks. wide, bears N. 80° E. and S. 80° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.162	The cor. of secs. 8, 9, 16, and 17, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 15x12x5 ins. (Thomas Record: 14x8x6 ins.), lying loose, mkd. with 4 grooves on a face and 4 grooves on another face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S 8 | S 9 S17 | S16 2025 Bury mkd. stone alongside stainless steel post.
	From the cor. of secs. 9, 10, 15, and 16. S. 89°30'50" W., bet. secs. 9 and 16.
0.95	Graded dirt road, 45 lks. wide, bears N. 70° E. and S. 70° W.
40.530	Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S 9 1/4 S16 2025
81.060	The cor. of secs. 8, 9, 16, and 17.
	From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy., T. 19 N., R. 30 E., executed concurrently under Group No. 1019.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 0°13'20" W., bet. secs. 31 and 32.
40.440	Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E 1/4 S31 | S32 2025
80.880	Point for the cor. of secs. 29, 30, 31, and 32, at proportionate distance based on the measurements from the unrecorded 1904 field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S30 | S29 S31 | S32 2025 From this point, two wood posts, both 3x3 ins.,4 ft. long, no marks visible, lying loose, bears SE., 17 lks. dist., and are not utilized during the course of this survey.
	From the cor. of secs. 28, 29, 32, and 33. N. 89°45'00" W., bet. secs. 29 and 32.
40.346	The 1/4 sec. cor. of secs. 29 and 32, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 12x10x7 ins. (Thomas Record: 12x6x6 ins.), firmly set, projecting 6 ins. above the ground, mkd. 1/4 on the N. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T20N R30E S29 1/4 —— S32 2025
	Bury mkd. stone alongside stainless steel post.
	N. 89°59'00" W., beginning new measurement.
40.276	The cor. of secs. 29, 30, 31, and 32.
	S. 89°30'10" W., bet. secs. 30 and 31.
40.150	The 1/4 sec. cor. of secs. 30 and 31, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 12x6x6 ins. (Thomas Record: 14x8x5 ins.), firmly set, projecting 6 ins. above the ground, mkd. 1/4 on the N. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R30E S30 1/4 —— S31 2025
	Bury mkd. stone alongside stainless steel post.
	S. 89°26'00" W., beginning new measurement.
38.468	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, mkd. as described in the field notes of the dependent resurvey of the E. bdy., T. 20 N., R. 29. E., executed concurrently under Group No. 1022.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the cor. of secs. 29, 30, 31, and 32.
	N. 0°06'30" W., bet. secs. 29 and 30.
28.70	Unimproved dirt road, 18 lks. wide, bears N. 75° E. and S. 75° W.
40.344	The 1/4 sec. cor. of secs. 29 and 30, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 14x10x5 ins. (Thomas Record: 12x8x4 ins.), firmly set, projecting 8 ins. above the ground, mkd. 1/4 on the W. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E 1/4 S30 | S29 2025 Bury mkd. stone alongside stainless steel post.
	N. 0°06'00" W., beginning new measurement.
40.380	The cor. of secs. 19, 20, 29, and 30, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 18x7x6 ins. (Thomas Record: 16x7x6 ins.), firmly set projecting 12 ins. above the ground, mkd. with 5 grooves on the E. face and 2 grooves on the S. face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S19 | S20 S30 | S29 2025 Bury mkd. stone alongside stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the cor. of secs. 20, 21, 28, and 29.
	S. 89°23'40" W., bet. secs. 20 and 29.
40.302	The 1/4 sec. cor. of secs. 20 and 29, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 11x8x5 ins. (Thomas Record: 12x6x5 ins.), lying loose, mkd. 1/4 on a face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S20 1/4 —— S29 2025
	Bury mkd. stone alongside stainless steel post.
	S. 89°29'30" W., beginning new measurement.
40.286	The cor. of secs. 19, 20, 29, and 30.
	N. 0°05'10" W., bet. secs. 19 and 20.
41.705	Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance, based on the measurements from the unrecorded 1904 field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E 1/4 S19|S20 2026

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.834	The cor. of secs. 17, 18, 19, and 20, perpetuated by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 13x13x3 ins. (Thomas Record: 14x8x5 ins.), lying loose, mkd. with 5 grooves on a face and 3 grooves on another face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as a careful and faithful perpetuation of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S18 | S17 S19 | S20 2025 The marked stone recovered during the course of this resurvey was not present at the time of remonumentation.
	From the cor. of secs. 16, 17, 20, and 21. S. 89°53'40" W., bet. secs. 17 and 20.
40.328	Point for the 1/4 sec. cor. of secs. 17 and 20 at proportionate distance, based on the measurements from the unrecorded 1904 field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R30E S17 1/4 S20 2026
80.646	The cor. of secs. 17, 18, 19, and 20.
	N. 0°01'50" W., bet. secs. 17 and 18.
33.90	Graded dirt road, 45 lks. wide, bears N. 80° E. and S 80° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

40.108 The 1/4 sec. cor. of secs. 17 and 18, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 13x7x5 ins. (Thomas Record: 14x6x5 ins.), lying horizonal, 12 ins. below the surface of the ground, mkd. 1/4 on a face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T20N R30E
1/4
S18|S17

2025

Bury mkd. stone alongside stainless steel post.

N. 0°13'20" W., beginning new measurement.

40.018 The cor. of secs. 7, 8, 17, and 18, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 15x10x4 ins. (Thomas Record: 14x6x6 ins.), lying horizontal, mkd. with 5 grooves on a face and 4 grooves on another face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T20N R30E
S 7|S 8

S18|S17

2025

Bury mkd. stone alongside stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the cor. of secs. 8, 9, 16, and 17.
	S. 89°42'50" W., bet. secs. 8 and 17.
40.320	The 1/4 sec. cor. of secs. 8 and 17, reestablished by A.H. Thomas, in 1904, for the USGS, monumented with a basalt stone, 12x7x4 ins. (Thomas Record: 12x6x6 ins.), lying loose, 18 ins. below the surface of the ground, mkd. 1/4 on a face, as described in the unrecorded field notes by A.H. Thomas on file with the Truckee-Carson Irrigation District, and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R30E S 8 1/4 —— S17
	2025
	Bury mkd. stone alongside stainless steel post.
	S. 89°50'30" W., beginning new measurement.
40.372	The cor. of secs. 7, 8, 17, and 18.

SUBDIVISION OF SECTION 14,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 0°06'40" E., on the N-S center line of sec. 14.
40.200	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R30E C 1/4 S14
	2025
74.35	Canal, 60 lks. wide, bears E. and SW.

SUBDIVISION OF SECTION 14,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.422	The 1/4 sec. cor. of secs. 11 and 14.
	From the 1/4 sec. cor. of secs. 13 and 14.
	N. 89°50'20" W., on the E-W center line of sec. 14.
40.672	The center 1/4 sec. cor. of sec. 14.
81.158	The 1/4 sec. cor. of secs. 14 and 15.

SUBDIVISION OF SECTION 15,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

	From the 1/4 sec. cor. of secs. 14 and 15.
	N. 89°43'30" W., on the E-W center line of sec. 15.
80.524	The 1/4 sec. cor. of secs. 15 and 16.

SUBDIVISION OF SECTION 16,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

	From the 1/4 sec. cor. of secs. 15 and 16.
	S. 89°31'30" W., on the E-W center line of sec. 16.
80.992	The 1/4 sec. cor. of secs. 16 and 17.

SUBDIVISION OF SECTION 17,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

	From the 1/4 sec. cor. of secs. 17 and 20.
	N. 0°04'50" W., on the N-S center line of sec. 17.
40.119	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R30E C 1/4 S17
	2025
48.15	Graded dirt road, 45 lks. wide, bears N. 35° E., and S. 35° W.

SUBDIVISION OF SECTION 17,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.164	The 1/4 sec. cor. of secs. 8 and 17.
	From the 1/4 sec. cor. of secs. 16 and 17.
	S. 89°52'50" W., on the E-W center line of secs. 17.
40.385	The center 1/4 sec. cor. of sec. 17.
46.15	Graded dirt road, 45 lks. wide, bears N. 35° E., and S. 35° W.
80.662	The 1/4 sec. cor. of secs. 17 and 18.

SUBDIVISION OF SECTION 23,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 0°06'30" W., on the N-S center line of sec. 23.
80.234	The 1/4 sec. cor. of secs. 14 and 23.

SUBDIVISION OF SECTION 26,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

	From the 1/4 sec. cor. of secs. 26 and 35, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above the ground, with an aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 20 N., R. 30 E., executed under Group No. 568.
	N. 0°06'40" W., on the N-S center line of sec. 26.
40.064	Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R30E C 1/4 S26 2025
80.178	The 1/4 sec. cor. of secs. 23 and 26.

SUBDIVISION OF SECTION 26,
T. 20 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the 1/4 sec. cor. of secs. 25 and 26.
	N. 89°56'20" W., on the E-W center line of sec. 26.
10.60	Canal, 50 lks. wide, bears N. and S.
40.808	The center 1/4 sec. cor. of sec. 26.
81.496	The 1/4 sec. cor. of secs. 26 and 27.

GENERAL DESCRIPTION

The land within Township 20 North, Range 30 East, is approximately 3,900 ft. above sea level and is nearly level land. During wet conditions there are numerous waterways and basins. The soil is a sandy clay loam and is covered with sagebrush and native grass.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Lance W. Smith	Nevada Professional Land Surveyor (Experiences Services Program)
Thomas D. Dockery	Supervisory Engine Captain
Robert S. Hollis	Survey Technician

CERTIFICATE OF SURVEY

I, Kelly R. Totten, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of February, 2025, I have dependently resurveyed a portion of the subdivisional lines and subdivided sections 14, 15, 16, 17, 23, and 26, Township 20 North, Range 30 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

SEP 18 2026
(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 14, 15, 16, 17, 23, and 26, Township 20 North, Range 30 East, of the Mount Diablo Meridian, Nevada, executed by Kelly R. Totten, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

SEP 25 2026
(Date)

Clarence D. Strickland
(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 20 North, Range 30 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~ ~~(Chief Cadastral Surveyor for Nevada)~~