

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE
SOUTH, EAST, WEST AND NORTH BOUNDARIES, AND
A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 22 NORTH, RANGE 30 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Richard J. Dieckmann, Cadastral Surveyor

Under Special Instructions dated May 29, 2025,

and approved May 29, 2025,

which provided for the surveys included under Group No. 1027,

and Assignment Instructions dated May 29, 2025.

Survey commenced June 3, 2025

Survey completed September 8, 2025

INDEX DIAGRAM

TOWNSHIP 22 NORTH, RANGE 30 EAST, MOUNT DIABLO MERIDIAN, NEVADA

	19	18	18	17	16	15	
13	6	5	4	3	2	25 1	9
						25	
13	7	8	9	10	11	24 12	8
						24	
12	18	17	16	15	14	23 13	8
						23	
12	19	20	21	22	23	22 24	7
						22	
11	30	29	28	27	26	21 25	7
						20	
10	31	32	33	34	35	19 36	6
	5	4	4	3	2	2	

TOWNSHIP 22 NORTH, RANGE 30 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of the south, east, west, and north boundaries, and a portion of the subdivisional lines, Township 22 North, Range 30 East, Mount Diablo Meridian, Nevada.

1882 - The south, east, west and north boundaries, and the subdivisional lines were surveyed by U.S. Deputy Surveyors G.W. Conkling Jr. and T.K. Stewart, under Contract Nos. 132 and 137.

1992 - The south and east boundaries were retraced and the corner of Townships 21 and 22 North, Ranges 30 and 31 East, was reestablished by R.A. Pratt, Cadastral Surveyor, under Group No. 728.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the position of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1027, dated May 29, 2025.

Measurements were made with Trimble R-10 Model 2, R-12 and R-12i Global Navigation Satellite System (GNSS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 83(2011)(EPOCH:2010.0000) geographic position, of the following corners, was determined from Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS):

AI8810 GARL GARL ECC REF DIMPLE,
AI8816 UPSA UPSA_BRGN_NV1997 ECCREF DIMPLE,
DH4796 TUNG TUNG_BRGN_NV1996 CORS MON,
DR8089 P129 DEADCOWPT_NV2007 CORS GRP,
DR8187 P069 INDIANPEAK_NV2006 CORS GRP
and carried forward by RTK observations

The corner of Townships 21 and 22 North, Ranges 30 and 31 East, is as follows:

Latitude: 39°43'25.178" N. Longitude: 118°33'00.843" W.

The corner of Townships 22 and 23 North, Ranges 29 and 30 East, is as follows:

Latitude: 39°48'39.460" N. Longitude: 118°39'48.262" W.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
TOWNSHIP 22 NORTH, RANGE 30 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Reestablishment of the Survey Executed by U.S. Deputy Surveyors G.W. Conkling Jr. and T.K. Stewart, in 1882
	Beginning at the cor. of Tps. 21 and 22 N., Rs. 30 and 31 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with a galvanized steel "U" post alongside, with brass cap mkd. as described in the field notes of the 1992 dependent resurvey of the W. bdy. of T. 21 N., R. 31 E., executed under Group No. 728. N. 89°43'10" W., bet. secs. 1 and 36.
40.347	Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S36 1/4 ——— S 1 T21N 2025
80.694	Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S35 S36 S 2 S 1 T21N 2025
	N. 89°43'10" W., bet. secs. 2 and 35.
40.347	Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
TOWNSHIP 22 NORTH, RANGE 30 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.694	T22N R30E S35 1/4 <u> </u> S 2 T21N 2025 Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S34 S35 S 3 S 2 T21N 2025
40.347	N. 89°43'10" W., bet. secs. 3 and 34. Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S34 1/4 <u> </u> S 3 T21N 2025
80.694	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S33 S34 S 4 S 3 T21N 2025

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
TOWNSHIP 22 NORTH, RANGE 30 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.347	N. 89°43'10" W., bet. secs. 4 and 33. Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S33 1/4 ——— S 4 T21N 2025
80.694	Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S32 S33 S 5 S 4 T21N 2025
40.347	N. 89°43'10" W., bet. secs. 5 and 32. Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S32 1/4 ——— S 5 T21N 2025
80.694	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
TOWNSHIP 22 NORTH, RANGE 30 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T22N R30E S31 S32 S 6 S 5 T21N 2025
40.347	N. 89°43'10" W., bet. secs. 6 and 31. Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S31 1/4 — S 6 T21N 2025
80.512	The cor. of Tps. 21 and 22 N., Rs. 29 and 30 E., determined by Wallace A. Cooper, Nevada Registered Land Surveyor No. 749, at an unknown date, monumented with a heavily oxidized iron pipe, length indeterminate, 3 1/2 ins. diam., firmly set, buried 24 ins. below the ground, with a 4 in. diam. heavily oxidized threaded plumbing cap mkd. LS 749 on the SW edge of the cap and the top mkd. N T22 N E 36 31 R30E W 1 6 E R29 S T21N No record found for this position. The pipe and cap is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., over a steel "T" post, inserted directly into the top of the broken heavily oxidized iron pipe, with a plastic-encased magnet set alongside the "T" post and under the stainless steel post, 23 ins. in the ground, in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
TOWNSHIP 22 NORTH, RANGE 30 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T22N R29N R30E S36 S31 S 1 S 6 T21N 2025 The plumbers cap which broke off during excavation was buried alongside the stainless steel post. Corner is located on the S. edge of a salt grass covered dune. DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of the Survey Executed by U.S. Deputy Surveyors G.W. Conkling Jr. and T.K. Stewart, in 1882 From the cor. of Tps. 21 and 22 N., Rs. 30 and 31 E., hereinbefore described. N. 0°07'40" W., bet. secs. 31 and 36. 40.052 <td> Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E R31E 1/4 S36 S31 2025 </td>	Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E R31E 1/4 S36 S31 2025
80.104	Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E R31E S25 S30 S36 S31 2025	

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°07'40" W., bet. secs. 25 and 30.
40.052	Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E R31E 1/4 S25 S30 2025
80.104	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E R31E S24 S19 S25 S30 2025
	N. 0°07'40" W., bet. secs. 19 and 24.
40.052	Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E R31E 1/4 S24 S19 2025
80.104	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T22N R30E R31E S13 S18 S24 S19 2025
40.052	N. 0°07'40" W., bet. secs. 13 and 18. Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
80.104	T22N R30E R31E 1/4 S13 S18 2025 Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
40.052	T22N R30E R31E S12 S 7 S13 S18 2025 N. 0°07'40" W., bet. secs. 7 and 12. Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T22N R30E R31E 1/4 S12 S 7 2025

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 80.104	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N <table style="margin: auto;"> <tr> <td>R30E</td><td>R31E</td></tr> <tr> <td>S 1</td><td>S 6</td></tr> <tr> <td>S12</td><td>S 7</td></tr> </table> 2025	R30E	R31E	S 1	S 6	S12	S 7
R30E	R31E						
S 1	S 6						
S12	S 7						
40.052	N. 0°07'40" W., bet. secs. 1 and 6. Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E R31E 1/4 S 1 S 6 2025						
80.104	Point for the cor. of Tps. 22 and 23 N., Rs. 30 and 31 E., at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T23N <table style="margin: auto;"> <tr> <td>R30E</td><td>R31E</td></tr> <tr> <td>S36</td><td>S31</td></tr> <tr> <td>S 1</td><td>S 6</td></tr> </table> T22N 2025 From this point, the cor. of Tps. 23 and 24 N., Rs. 30 and 31 E., bears N. 0°37'00" W., 480.651 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the 1992 dependent resurvey of the W. bdy. of T. 21 N., R. 31 E., executed under Group No. 728.	R30E	R31E	S36	S31	S 1	S 6
R30E	R31E						
S36	S31						
S 1	S 6						

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The control line was fully retraced and careful search was made for evidence of the intervening corners, none of which were recovered.

From this same point, the cor. of Tps. 22 and 23 N., Rs. 32 and 33 E., bears N. $89^{\circ}41'30''$ E., 961.554 chs. dist., determined 1 1/2 ft. N. from the center of a scattered mound of stone, 10 ft. diam. This position correlates well with the measurement reported from the cor. of Tps. 22 and 23 N., R. 33 E., in the field notes of the 1930-32 dependent resurvey of the W. bdy. of T. 23 N., R. 34 E., executed under Group No. 153, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.

T23N	
R32E	R33E
S36	S31
S 1	S 6
T22N	

2025

The control line was fully retraced and careful search was made for evidence of the intervening corners, none of which were recovered.

From this corner, the cor. of Tps. 22 and 23 N., R. 33 E., bears S. $89^{\circ}47'10''$ E., 478.353 chs. dist. (1930-32 record, S. $89^{\circ}58'$ E., 478.65 chs. dist.), monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above the ground, in a mound of stone, 3 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy. of T. 23 N., R. 34 E., executed under Group No. 153.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by U.S. Deputy Surveyors
G.W. Conkling Jr. and T.K. Stewart, in 1882

From the cor. of Tps. 21 and 22 N., Rs. 29 and 30 E., hereinbefore described.

N. $0^{\circ}11'10''$ E., bet. secs. 31 and 36.

39.963

Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R29E R30E 1/4 S36 S31 2025
79.926	Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T22N R29E R30E S25 S30 S36 S31 2025
39.963	N. 0°11'10" E., bet. secs. 25 and 30. Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T22N R29E R30E 1/4 S25 S30 2025
79.926	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R29E R30E S24 S19 S25 S30 2025

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°11'10" E., bet. secs. 19 and 24.
39.963	Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R29E R30E 1/4 S24 S19 2025
79.926	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R29E R30E S13 S18 S24 S19 2025 From this point, a well casing 12 ins. diam., with an 8 in. diam. sleeve, projecting 8 ins. above ground, bears N. 41°00' E., 12.80 chs. dist.
	N. 0°11'10" E., bet. secs. 13 and 18.
39.963	Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T22N R29E R30E 1/4 S13 S18 2025
79.926	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T22N R29E R30E S12 S 7 S13 S18 2025
39.963	N. 0°11'10" E., bet. secs. 7 and 12. Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.
79.926	T22N R29E R30E 1/4 S12 S 7 2025 Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.
39.963	T22N R29E R30E S 1 S 6 S12 S 7 2025 N. 0°11'10" E., bet. secs. 1 and 6. Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.
	T22N R29E R30E 1/4 S 1 S 6 2025

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

79.926

Point for the cor. of Tps. 22 and 23 N., Rs. 29 and 30 E., at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T23N	
R29E	R30E
S36	S31
S 1	S 6
T22N	

2025

From this point, the cor. of Tps. 22 and 23 N., Rs. 28 and 29 E., bears S. 89°46'50" W., 480.847 chs. dist., determined by Randal Briggs, Nevada Professional Land Surveyor No. 7998, at an unknown date, monumented with a rebar, 24 ins. long, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with a yellow plastic cap mkd. PLS 7998, no record found. This position correlates well with the position shown on a Map titled, "Map to Accompany Application to Appropriate Water for Milling and Mining Purposes", by Lowell D. Emery, Nevada Registered Land Surveyor No. 1251, in 1983, on file with the Nevada Division of Water Resources, document no. 45929, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.

T23N	
R28E	R29E
S36	S31
S 1	S 6
T22N	

2025

Bury the rebar inside the stainless steel post.

The control line was fully retraced and careful search was made for evidence of the intervening corners, none of which were recovered.

From this same point, the cor. of Tps. 23 and 24 N., Rs. 29 and 30 E., bears N. 0°24'30" W., 479.564 chs. dist., monumented with a granite stone, 23x10x3 ins. (Record, 20x12x4 ins.), loosely set in the center of a mound of stone, 3 ft. diam., 1/2 ft. high, mkd. with 6 horizontal grooves on N, E, S and W faces.

At the corner point

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T24N R29E R30E S36 S31 S 1 S 6 T23N 2025 Bury the original stone alongside the stainless steel post. The control line was fully retraced and careful search was made for evidence of the intervening corners, none of which were recovered. DEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of the Survey Executed by U.S. Deputy Surveyors G.W. Conkling Jr. and T.K. Stewart, in 1882 From the cor. of Tps. 22 and 23 N., Rs. 30 and 31 E., hereinbefore described. N. 89°50'40" W., bet. secs. 1 and 36. 40.183 Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T23N R30E S36 1/4 — S 1 T22N 2025 80.366 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
--------	---

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T23N R30E $\frac{S35}{S\ 2} \frac{S36}{S\ 1}$ T22N 2025
21.860	N. 89°50'40" W., bet. secs. 2 and 35. Point for a witness point, at intersection with the line of the B-20 Range Boundary as determined by Jimmy J. Elmore, Nevada Professional Land Surveyor No. 32991, in 2025, shown on Record of Survey recorded in Churchill County, Nevada, Book 32, Pages 1-22, File No. 517459, and in Pershing County, Nevada, Document No. 532974. This witness point will function as an angle point, established by public law 117-263, of the B-20 Range Boundary. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. WP T23N R30E $\frac{S35}{S\ 2}$ T22N R30E 2025 From this point, a point established as an angle point, of the B-20 Range Boundary, by Jimmy J. Elmore, Nevada Professional Land Surveyor No. 32991, in 2025, monumented with an alum. rod, 1 in. diam., firmly set, projecting 4 ins. above the ground, with a 3 1/4 in. diam. alum. cap, mkd. AP $\swarrow$ B 20 RNG PLS 32991 2025, being Monument No. 4301, shown on Record of Survey, recorded in Churchill County, Nevada, Book 32, Pages 1-22, File No. 517459, and in Pershing County, Nevada, Document No. 532974, bears N. 32°36'50" E., 35.306 chs. dist. From this same point, a point established as a witness point, on the prolongation of the calculated B-20 Range Boundary, by Jimmy J. Elmore, Nevada Professional Land Surveyor No. 32991, in 2025, monumented with an alum. rod, 1 in. diam., firmly set, projecting 4 ins. above the ground, with a 3 1/4 in. diam. alum. cap, mkd. WP $\bullet$ PLS 32991 2025, being Monument No. 4407, shown on Record of Survey recorded in Churchill County, Nevada, Book 32, Pages 1-22, File No. 517459, and in Pershing County, Nevada, Document No. 532974, bears S. 32°36'40" W., 44.709 chs. dist.
40.183	Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T23N R30E S35 1/4 ——— S 2 T22N 2025
80.366	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T23N R30E S34 S35 S 3 S 2 T22N 2025
40.183	N. 89°50'40" W., bet. secs. 3 and 34. Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T23N R30E S34 1/4 ——— S 3 T22N 2025
80.366	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T23N R30E S33S34 S 4S 3 T22N 2025 N. 89°50'40" W., bet. secs. 4 and 33. 40.183 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T23N R30E S33 1/4 S 4 T22N 2025 80.366 Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T23N R30E S32S33 S 5S 4 T22N 2025 N. 89°50'40" W., bet. secs. 5 and 32. 40.183 Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
--------	--

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.366	T23N R30E S32 1/4 — S 5 T22N 2025 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T23N R30E S31 S32 S 6 S 5 T22N 2025
40.183	N. 89°50'40" W., bet. secs. 6 and 31. Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T23N R30E S31 1/4 — S 6 T22N 2025
78.920	The cor. of Tps. 22 and 23 N., Rs. 29 and 30 E., hereinbefore described. DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors G.W. Conkling Jr. and T.K. Stewart, in 1882 From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described. N. 0°03'20" E., bet. secs. 35 and 36.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.025	Point for the 1/4 sec. cor. of secs. 35 and 36 at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E 1/4 S35 S36 2025
80.050	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S26 S25 S35 S36 2025 From this point, the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., bears N. 89°44'10" W., 403.017 chs. dist., hereinbefore described. The control line was fully retraced and careful search was made for evidence of the intervening corners, none of which were recovered. From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described. N. 89°45'20" W., bet. secs. 25 and 36.
40.211	Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S25 1/4 ——— S36 2025
80.422	The cor. of secs. 25, 26, 35 and 36.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°07'30" W., bet. secs. 25 and 26.
40.026	Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E 1/4 S26 S25 2025
40.136	Point for a witness point, at intersection with the line for the B-20 Range Boundary as determined by Jimmy J. Elmore, Nevada Professional Land Surveyor No. 32991, in 2025, shown on Record of Survey recorded in Churchill County, Nevada, Book 32, Pages 1-22, File No. 517459, and in Pershing County, Nevada, Document No. 532974. This witness point will function as an angle point, established by public law 117-263, of the B-20 Range Boundary. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. WP T22N R30E S26 S25 2025 From this point, a point established as an angle point of the B-20 Range Boundary, by Jimmy J. Elmore, Nevada Professional Land Surveyor No. 32991, in 2025, monumented with an alum. rod, 1 in. diam., firmly set, projecting 4 ins. above the ground, with a 3 1/4 in. diam. alum. cap, mkd. AP ●/ B 20 RNG PLS 32991 2025, being Monument No. 4406, shown on Record of Survey recorded in Churchill County, Nevada, Book 32, Pages 1-22, File No. 517459, and in Pershing County, Nevada, Document No. 532974, bears S. 57°54'00" E., 28.009 chs. dist. From this same point, a point established as a witness point on the prolongation of the calculated B-20 Range Boundary, by Jimmy J. Elmore, Nevada Professional Land Surveyor No. 32991, in 2025, monumented with an alum. rod, 1 in. diam., firmly set, projecting 4 ins. above the ground, with a 3 1/4 in. diam. alum. cap, mkd. WP ●/ PLS 32991 2025, being Monument No. 4457, shown on Record of Survey recorded in Churchill County, Nevada, Book 32, Pages 1-22, File No. 517459, and in Pershing County, Nevada, Document No. 532974, bears N. 57°54'20" W., 52.006 chs. dist.
80.052	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S23 S24 S26 S25 2025 From this point, the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., bears N. 89°45'20" W., 402.498 chs. dist., hereinbefore described. The control line was fully retraced and careful search was made for evidence of the intervening corners, none of which were recovered. From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described. N. 89°47'40" W., bet. secs. 24 and 25.
40.201	Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S24 1/4 ——— S25 2025
80.402	The cor. of secs. 23, 24, 25 and 26. N. 0°04'40" W., bet. secs. 23 and 24.
40.025	Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T22N R30E 1/4 S23 S24 2025
80.050	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S14 S13 S23 S24 2025 From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears N. 89°46'20" W., 402.045 chs. dist., hereinbefore described. The control line was fully retraced and careful search was made for evidence of the intervening corners, none of which were recovered. From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described. N. 89°49'50" W., bet. secs. 13 and 24. 40.159 Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S13 1/4 ——— S24 2025 80.318 The cor. of secs. 13, 14, 23 and 24. N. 0°04'10" W., bet. secs. 13 and 14. 40.025 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E 1/4 S14 S13 2025
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 80.050	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E $\frac{S11}{S14} \frac{S12}{S13}$ 2025 From this point, a hot spring approximately 5 ft. diam., bears S. 73°31' W., 47.10 chs. dist. From this same point, the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., bears N. 89°47'20" W., 401.606 chs. dist., hereinbefore described. The control line was fully retraced and careful search was made for evidence of the intervening corners, none of which were recovered. From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described. N. 89°52'10" W., bet. secs. 12 and 13.
40.110	Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T22N R30E S12 1/4 ——— S13 2025
80.220	The cor. of secs. 11, 12, 13 and 14. N. 0°09'50" W., bet. secs. 11 and 12.
40.026	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T22N R30E 1/4 S11 S12 2025
80.052	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S 2 S 1 S11 S12 2025 From this point, the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., bears N. 89°48'30" W., 401.036 chs. dist., hereinbefore described. The control line was fully retraced and careful search was made for evidence of the intervening corners, none of which were recovered. From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described. N. 89°54'20" W., bet. secs. 1 and 12.
40.127	Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E S 1 1/4 ——— S12 2025
80.254	The cor. of secs. 1, 2, 11 and 12. N. 0°13'10" W., bet. secs. 1 and 2.
40.026	Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T22N R30E 1/4 S 2 S 1 2025
80.192	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described. GENERAL DESCRIPTION The area surveyed is northeast of Fallon, Nevada, in the Carson Sink, a large alkali lake bed that is subject to seasonal inundation. The Carson River flows into the sink from the south and the Humboldt River flows into the sink from the west. There is extremely sparse vegetation near the southerly extent of the township consisting of salt grass in scattered sand dunes. Signs of prior/past human activity include abandoned tires, military munitions and heavily oxidized metal machine parts that are almost indiscernible in function. The average elevation is approximately 3,900 ft. above mean sea level.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Lance W. Smith

Nevada Professional Land Surveyor
(Experienced Services Program)

CERTIFICATE OF SURVEY

I, Richard J. Dieckmann, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing the date of the 29th day of May, 2025, I have dependently resurveyed the South, East, West and North boundaries, and a portion of the subdivisional lines, Township 22 North, Range 30 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUL 14 2026

(Date)

Richard J. Dieckmann
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the South, East, West and North boundaries, and a portion of the subdivisional lines, Township 22 North, Range 30 East, of the Mount Diablo Meridian, Nevada, executed by Richard J. Dieckmann, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUL 17 2026

(Date)

Clarence D. Strickland
(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 22 North, Range 30 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~