

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
OF TOWNSHIP 40 NORTH, RANGE 27 EAST,
AND THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
THE SURVEY OF PORTIONS OF THE EAST AND NORTH BOUNDARIES
AND A PORTION OF THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF SECTIONS 16, 17, 18, 20, AND 21,
AND A METES-AND-BOUNDS SURVEY OF A PORTION OF THE
BLACK ROCK DESERT WILDERNESS BOUNDARY
THROUGH SECTIONS 5, 6, 7, 8, AND 18,
TOWNSHIP 40 NORTH, RANGE 28 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Kelly R. Totten, Cadastral Surveyor

Under Special Instructions dated August 12, 2025,
and approved August 12, 2025,
which provided for the surveys included under Group No. 1031,
and Assignment Instructions dated August 12, 2025.

Survey commenced September 9, 2025

Survey completed October 25, 2025

INDEX DIAGRAM

TOWNSHIP 40 NORTH, RANGE 28 EAST, MOUNT DIABLO MERIDIAN, NEVADA

1	5	13	12				
		27 6	27 5	22 4	3	2	1
		26	25				
12	4	26 7	25 8	21 9	10	11	12
		24	22	19	15		
13	4	24 18	23 17	20 16	17 15	14	13
		11	10	8 7	16		
24	3	19 19	9 20	6 21	16 22	23	24
		8	21	18 19			
25	2	30 30	20 29	17 28	14 27	26	25
36		31 31	32 32	33 33	34 34	35 35	36 36
							11

SUBDIVISION OF SECTION 16	pp 28
SUBDIVISION OF SECTION 17	pp 28
SUBDIVISION OF SECTION 18	pp 28
SUBDIVISION OF SECTION 20	pp 29 - 30
SUBDIVISION OF SECTION 21	pp 30
METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT	
WILDERNESS BOUNDARY THROUGH SECTIONS 5, 6, 7, 8, AND 18.....	pp 31 - 45

TOWNSHIP 40 NORTH, RANGE 28 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the east boundary of Township 40 North, Range 27 East, and the dependent resurvey of a portion of the subdivisional lines, the survey of portions of the east and north boundaries and a portion of the subdivisional lines, the subdivision of sections 16, 17, 18, 20, and 21, and a metes-and-bounds survey of a portion of the Black Rock Desert Wilderness Boundary through sections 5, 6, 7, 8, and 18, Township 40 North, Range 28 East, Mount Diablo Meridian, Nevada.

1873 - The Eighth Standard Parallel North, through Ranges 27 and 28 East, the west boundary, and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyors W.W. Skinner, G.W. Garside, and C.S. Preble, under joint Contract No. 58.

1915 - The Eighth Standard Parallel North, through a portion of Ranges 27 and 28 East was resurveyed by U.S. Surveyor W.E. Hoffman, under Group No. 35.

1920 - The Seventh Standard Parallel North, through Range 28 East, was surveyed by U.S. Cadastral Engineer E. Voigt, under Group No. 83

1951 - The Eighth Standard Parallel North, through a portion of Range 27 East, a portion of the east boundary and a portion of the subdivisional lines of Township 40 North, Range 27 East, were resurveyed, and a portion of the subdivisional lines of Township 40 North, Range 28 East were retraced by Cadastral Engineers R.F. Wilson and E.A. Taylor, under Group No. 220.

1964 - Nevada Protraction Diagram Nos. 263, 264, and 265, Unit No. 19, were approved February 3, 1964.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the position of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1031, dated August 12, 2025.

Measurements were made with Trimble R12i and R10-2 Global Navigation Satellite System (GNSS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

TOWNSHIP 40 NORTH, RANGE 28 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	The NAD 83(2011)(EPOCH:2010.0000) geographic position, of the following corners were determined from Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS); DL7715 P013 SPRINGCREKNV2007 CORS GRP, AI8810 GARL GARL ECC REF DIMPLE, AJ6964 SHLD SHLD PNGA NV1999 CORS MONUMENT, DH4796 TUNG TUNG BRGN NV1996 CORS MON, DH4795 BURN BURN PNGA OR1998 CORS MRP, DR8086 P083 NEEDLEPEAKNV2007 CORS GRP, DN7469 P731 LILJUNIPERCN2007 CORS GRP, DK6486 MODB MODOC PLATEAU CORS GRP, DP9277 P018 PHARMACY OR2008 CORS GRP, and carried forward by RTK observations. The corner of Tps. 39 1/2 and 40 N., R. 28 E., is as follows: Latitude: 41°19'07.391" N. Longitude: 118°43'36.654" W. The standard corner of Tp. 41 N., R. 27 E., and the NE. corner of Tp. 40 N., R. 27 E., is as follows: Latitude: 41°24'34.773" N. Longitude: 118°49'36.341" W. DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 40 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors W.W. Skinner, G.W. Garside, and C.S. Preble in 1873 and the Resurvey Executed by Cadastral Engineers R.F. Wilson and E.A. Taylor in 1951 Beginning at the cor. of secs. 25, 30, 31, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the top of an embedded mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the resurvey of a portion of the E. bdy. of T. 40 N., R. 27 E., executed under Group No. 220. N. 0°21'00" W. bet. secs. 25 and 30. 25.20 Dry Bed of Battle Creek, 12 lks. wide, 3 ft. deep, drains winding SE. 42.149 The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the top of an embedded mound of stone, 2 ft. diam., with brass cap mkd. as described in the field notes of the resurvey of a portion of the E. bdy. of T. 40 N., R. 27 E., executed under Group No. 220. Remark brass cap to read
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 40 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T40N R27E R28E 1/4 S25 S30 2025 1951 N. 0°22'10" W., beginning new measurement. 8.90 Dry bed of Battle Creek, 8 lks. wide, 2 ft. deep, drains SW. Thence along mean course of a dry channel flowing into Battle Creek, 8 lks. wide, 1 ft. deep. 41.60 Leave dry channel, drains winding S. from the NE. 42.153 The cor. of secs. 19, 24, 25, and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the resurvey of a portion of the E. bdy. of T. 40 N., R. 27 E., executed under Group No. 220. N. 0°22'40" W. bet. secs. 19 and 24. 42.147 The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the top of an embedded mound of stone, 2 ft. diam., with brass cap mkd. as described in the field notes of the resurvey of a portion of the E. bdy. of T. 40 N., R. 27 E., executed under Group No. 220. Remark brass cap to read T40N R27E R28E 1/4 S24 S19 2025 1951 N. 0°21'50" W., beginning new measurement. 24.75 Graded dirt road, 30 lks. wide, bears S. 75° E. and N. 75° W. 42.165 The cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the top of an embedded mound of stone, 2 ft. diam., with brass cap mkd. as described in the field notes of the resurvey of a portion of the E. bdy. of T. 40 N., R. 27 E., executed under Group No. 220.
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 40 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°22'40" W. on the E. bdy. of sec. 13.
12.40	Dry contributory channel of Battle Creek, 9 lks. wide, 3 ft. deep, drains winding SE.
42.157	The 1/4 sec. cor. of sec. 13 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the top of an embedded mound of stone, 2 ft. diam., with brass cap mkd. as described in the field notes of the resurvey of a portion of the E. bdy. of T. 40 N., R. 27 E., executed under Group No. 220. This cor. will now refer to secs. 13 and 18. Remark brass cap to read T40N R27E R28E 1/4 S13 S18 2025 1951
	N. 0°22'20" W., beginning new measurement.
29.233	The cor. of secs. 7 and 18 only, T. 40 N., R. 28 E., hereinafter described.
42.154	The cor. of secs. 12 and 13 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the top of an embedded mound of stone, 2 ft. diam., with brass cap mkd. as described in the field notes of the resurvey of a portion of the E. bdy. of T. 40 N., R. 27 E., executed under Group No. 220. Remark brass cap to read T40N S12 S13 R27E T40N R28E S 7 2025 1951
	N. 0°22'50" W. on the E. bdy. of sec. 12.
27.080	The 1/4 sec. cor. of sec. 7 only, T. 40 N., R. 28 E., hereinafter described.
42.144	The 1/4 sec. cor. of sec. 12 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above the top of an embedded mound of stone, 2 ft. diam., with brass cap mkd. as described in the field notes of the resurvey of a portion of the E. bdy. of T. 40 N., R. 27 E., executed under Group No. 220, with a steel fence post alongside.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 40 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Remark brass cap to read T40N R27E R28E 1/4 S12 2025 1951 N. 0°22'30" W., beginning new measurement.
24.936	The cor. of secs. 6 and 7 only, T. 40 N., R. 28 E., hereinafter described.
35.55	Faint rut road, 15 lks. wide, bears N. 30° E. and S. 30° W.
42.157	The cor. of secs. 1 and 12 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the top of an embedded mound of stone, 2 ft. diam., with brass cap mkd. as described in the field notes of the resurvey of a portion of the E. bdy. of T. 40 N., R. 27 E., executed under Group No. 220. Remark brass cap to read T40N S 1 T40N — R28E S12 S 6 R27E 1951 2025 N. 0°22'30" W. on the E. bdy. of sec. 1.
22.779	The 1/4 sec. cor. of sec. 6 only, T. 40 N., R. 28 E., hereinafter described.
42.158	The 1/4 sec. cor. of sec. 1 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above the top of an embedded mound of stone, 2 ft. diam., with brass cap mkd. as described in the field notes of the resurvey of a portion of the E. bdy. of T. 40 N., R. 27 E., executed under Group No. 220. Remark brass cap to read T40N R27E R28E 1/4 S 1 2025 1951

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 40 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°22'30" W., beginning new measurement.
11.90	Trail road, 15 lks. wide, bears S. 85° E. and N. 85° W.
13.400	The witness point, at the intersection of the Black Rock Wilderness Area Boundary, with the E. bdy. of sec. 1, hereinafter described.
20.622	The cor. of Tps. 40 and 40 1/2 N., R. 28 E., hereinafter described.
41.35	Top of low rise, bears N. 85° E. and S. 85° W.
42.778	The standard corner of T. 41 N., R. 27 E., and NE. cor. of T. 40 N., R. 27 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the resurvey of a portion of the Eight Standard Parallel North, along the S. bdy. of T. 41 N., R. 27 E., executed under Group No. 220, evidence of a trench 3 ft. diam. around iron post.
	Remark brass cap to read
	SC T41N R27E S36 T40 1/2N — R28E S 1 S31 T40N
	2025 1951
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of the Survey Executed by U.S. Deputy Surveyors W.W. Skinner, G.W. Garside, and C.S. Preble in 1873 From the cor. of secs. 16, 17, 20, and 21, monumented with a limestone, 18x11x4 ins., firmly set, projecting 4 ins. above the ground, marked with 3 notches on the S. edge (Record: granite stone, 18x7x4 ins., mkd. 3 notches on S. and 4 notches on E.), in a mound of stone, 3 ft. diam., 1 ft. high. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T40N R28E S17 S16 S20 S21 2025
	Bury marked stone alongside the stainless steel post. SOUTH, bet. secs. 20 and 21.
20.000	Point for the N 1/16 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. N 1/16 S20 S21 2025
40.000	Point for the 1/4 sec. cor. of secs. 20 and 21, determined at record bearing and distance from the cor. of secs. 16, 17, 20, and 21; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base, to top with brass cap mkd. T40N R28E 1/4 S20 S21 2025 From the cor. of secs. 16, 17, 20, and 21. EAST, bet. secs. 16 and 21.
40.000	Point for the 1/4 sec. cor. of secs. 16 and 21, determined at record bearing and distance from the cor. of secs. 16, 17, 20, and 21; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E S16 1/4 ——— S21 2025

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the cor. of secs. 16, 17, 20, and 21. NORTH, bet. secs. 16 and 17.
40.000	Point for the 1/4 sec. cor. of secs. 16 and 17, determined at record bearing and distance from the cor. of secs. 16, 17, 20, and 21; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E 1/4 S17 S16 2025 From the cor. of secs. 19, 20, 29, and 30, monumented with a lava stone, 16x8x4 ins., lying loose in a small mound of stone, marked with 5 grooves on a face (Record: granite stone, mkd. with 2 notches on S. and 5 notches on E.). This cor. will now refer to secs. 19 and 30 only. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E S19 S30 S29 2025 Bury the mkd. stone alongside the stainless steel post. N. 89°31'30" W. bet. secs. 19 and 30.
14.75	Base of bluff, bears S. 20° E. and N. 20° W.
42.660	The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the retracement of a portion of the boundaries of section 30, T. 40 N., R. 28 E., executed under Group No. 220. Remark brass cap to read

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T40N R28E S19 1/4 <u> </u> S30 1951 2025 N. 79°18'10" W., beginning new measurement.
44.698	The cor. of secs. 19, 24, 25, and 30, on the E. bdy. of T. 40 N., R. 27 E., hereinbefore described. From the cor. of secs. 19 and 30 only. N. 0°40'40" W., on the E. bdy. of sec. 19.
4.349	The cor. of secs. 20 and 29 only, hereinafter described.
41.870	The 1/4 sec. cor. of secs. 19 and 20, determined at the center of a mound of stone, 4 ft. diam., 1 ft. high, with a granite stone 16x6x4 ins. lying loose alongside the mound, no marks visible. (Record: 16x7x7 ins., mkd. 1/4 on W. side). This is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E 1/4 S19 S20 2025 From this corner, the head of West Pinto Hot Spring, bears N. 52°33' W., 23.40 chs. dist., flows westerly. N. 2°53'50" W. beginning new measurement.
2.90	Graded dirt road, 18 lks. wide, bears N. 85° E. and N. 70° W.
30.10	Base of hill, bears, N. 85° E. and S. 85° W.
40.051	Point for the cor. of secs. 17, 18, 19, and 20, determined by the method of three point control; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T40N R28E S18 S17 S19 S20 2025
	From the cor. of secs. 16, 17, 20, and 21. S. 89°02'30" W. bet. secs. 17 and 20.
10.80	From this point, one of the heads of Pinto Hot Springs, bears NORTH, 3.30 chs. dist., flows southerly then easterly.
14.50	From this point, one of the heads of Pinto Hot Springs, bears NORTH, 1.80 chs. dist., flows SE. in a manmade ditch.
19.310	Point for the E 1/16 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 5 ft. base to top, with brass cap mkd. S17 E 1/16 S20 2025
27.45	Trail road, 15 lks. wide, bears N. 75° E. and S. 65° W.
27.90	Trail road, 15 lks. wide, bears N. 40° E. and S. 50° W.
38.620	The 1/4 sec. cor. of secs. 17 and 20, monumented with granite stone, 18x6x4 ins., no marks visible (Record: 12x4x4 ins., mkd. 1/4 on N. side), loosely set in a mound of stone, 4 ft. diam., 1 ft. high. This is accepted as the best available evidence of the position of the original corner. At the corner Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 4 ft. base to top, with brass cap mkd. T40N R28E S17 1/4 S20 2025

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°20'00" W., beginning new measurement.
43.700	The cor. of secs. 17, 18, 19, and 20.
	N. 82°31'40" W. bet. secs. 18 and 19.
20.00	Base of hill, bears N. 5° E. and S. 5° W.
32.90	Trail road, 15 lks. wide, bears S. 10° E. and N. 10° W.
44.070	Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T40N R28E S18 1/4 ——— S19 2025
85.309	The cor. of secs. 13, 18, 19, and 24, on the E. bdy. of T. 40 N., R. 27 E., hereinbefore described.
	SURVEY OF A PORTION OF THE EAST BOUNDARY, T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA From the point for the cor. of secs. 25 and 36 only, determined EAST from the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of T. 40 N., R. 27 E., hereinbefore described, and NORTH from the standard corner of Tps. 36 N., Rs. 28 and 29 E. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N S25 ——— S36 R28E T40N R29E S30 2025 From this point, the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of T. 40 N., R. 27 E., bears WEST, 413.101 chs. dist., hereinbefore described. SOUTH, on the E. bdy. of sec. 36.
40.000	Point for the 1/4 sec. cor. of sec. 36 only.

SURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E R29E 1/4 S36 2025
80.000	Point for the cor. of Tps. 39 1/2 and 40 N., R. 28 E. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E S36 T40N — R29E S36 S31 T39 1/2N 2025 From this point, the standard corner of Tps. 36 N., Rs. 28 and 29 E., bears SOUTH, 1975.295 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the Seventh Standard Parallel North through Range 28 East, executed under Group No. 83. SURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA From the point for the cor. of secs. 4, 5, 32, and 33, determined WEST, 320.000 chs. dist. and N. 00°02'20" W., 400.000 chs. dist., from the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., hereinbefore described. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40 1/2N R28E S32 S33 — S 5 S 4 T40N 2025

SURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From this point, the cor. of secs. 25, and 36 only, on the E. bdy. of the Tp., bears S. 38°40'00" E., 512.305 chs. dist., hereinbefore described. WEST, bet. secs. 5 and 32.
40.000	Point for the 1/4 sec. cor. of secs. 5 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40 1/2N R28E S32 1/4 ——— S 5 T40N 2025
41.00	Closed trail road, 12 lks. wide, bears N. 55° E. and S. 55° W.
80.000	Point for the cor. of secs. 5, 6, 31, and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base to top, with brass cap mkd. T40 1/2N R28E S31 S32 S 6 S 5 T40N 2025
15.322	WEST, bet secs. 6 and 31. Intersect the E. bdy. of sec. 1, T. 40 N., R. 27 E. Point for the cor. of Tps. 40 and 40 1/2 N., R. 28 E. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.

SURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T40 1/2N R28E T40N S31 R27E S 1 S 6 T40N 2025 From this point, the 1/4 sec. cor. of sec. 1 only on the E. bdy. of T. 40 N., R. 27 E., bears S. 0°22'30" E., 20.622 chs. dist., hereinbefore described. SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA From the point for the cor. of secs. 22, 23, 26, and 27, determined WEST, 160.000 chs. dist. and N. 00°00'50" E., 80.000 chs. dist., from the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., hereinbefore described. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T40N R28E S22 S23 S27 S26 2025 From this point, the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., bears S. 63°26'10" E., 178.885 chs. dist., hereinbefore described. WEST, on the N. bdy. of sec. 27. 7.168 The cor. of secs. 21 and 22 only, hereinafter described. 40.000 Point for the 1/4 sec. cor. of sec. 27 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T40N R28E 1/4 S27 2025 47.168 The 1/4 sec. cor. of sec. 21 only, hereinafter described. 80.000 Point for the cor. of secs. 27 and 28 only.
--------	---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base to top, with brass cap mkd. T40N R28E S21 S28 S27 2025 From the point for the cor. of secs. 10, 11, 14, and 15, determined WEST, 160.000 chs. dist. and N. 00°00'50" E., 240.000 chs. dist., from the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., hereinbefore described. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, in a supporting mound of stone, 6 ft. base to top, with brass cap mkd. T40N R28E S10 S11 S15 S14 2025 From this point, the cor. of secs. 25, and 36 only, on the E. bdy. of the Tp., bears S. 33°41'20" E., 288.444 chs. dist., hereinbefore described. WEST, on the S. bdy. of sec. 10. 7.094 The cor. of secs. 15 and 16 only, hereinafter described. 40.000 Point for the 1/4 sec. cor. of sec. 10 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E 1/4 S10 2025 47.094 The 1/4 sec. cor. of sec. 16 only, hereinafter described. 80.000 Point for the cor. of secs. 9 and 10 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.
--------	---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T40N R28E S 9 S10 S16 2025 From the 1/4 sec. cor. of secs. 16 and 21, hereinbefore described. EAST, bet. secs. 16 and 21. 40.000 Point for the cor. of secs. 16 and 21 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E S16 S21 S22 2025 S. 00°00'50" W., on the E. bdy. of sec. 21. 40.000 Point for the 1/4 sec. cor. of sec. 21 only, determined at 40.00 chs. in latitude from the cor. of secs. 16 and 21 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E S21 1/4 2025 78.672 Intersect the N. bdy. of sec. 27. Point for the cor. of secs. 21 and 22 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T40N R28E S21 S22 S27 2025
--------	---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From this point, the cor. of secs. 22, 23, 26, and 27, bears East, 7.168 chs. dist. From the cor. of secs. 16 and 21 only. N. 00°00'50" E., on the E. bdy. of sec. 16.
40.000	Point for the 1/4 sec. cor. of sec. 16 only, determined at 40.00 chs. in latitude from the cor. of secs. 16 and 21 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E 1/4 S16 2025
81.328	Intersect the S. bdy. of sec. 10. Point for the cor. of secs. 15 and 16 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 5 ft. base to top, with brass cap mkd. T40N R28E S10 S16 S15 2025 From this point, the cor. of secs. 10, 11, 14, and 15, bears East, 7.094 chs. dist. From the cor. of secs. 27 and 28 only. WEST, on the N. bdy. of sec. 28.
7.168	The cor. of secs. 20 and 21 only, hereinafter described.
40.000	Point for the 1/4 sec. cor. of sec. 28 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T40N R28E 1/4 S28 2025 47.098 The 1/4 sec. cor. of sec. 20 only, hereinafter described. 80.000 Point for the cor. of secs. 28 and 29 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E S20 S29 S28 2025 From the 1/4 sec. cor. of secs. 20 and 21, hereinbefore described. SOUTH, bet. secs. 20 and 21. 16.10 Base of mountain, bears S. 65° E. and N. 65° W. 38.672 Intersect the N. bdy. of sec. 28. Point for the cor. of secs. 20 and 21 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E S20 S21 S28 2025 From this point, the cor. of secs. 27 and 28 only, bears East, 7.168 chs. dist. From this same point, United States Coast and Geodetic Survey benchmark "BATTLE" bears S. 19°09'00" W., 45.045 chs. dist., monumented with a bronze disk, 3 1/2 ins. diam., firmly cemented into a drill hole in a rock outcrop, with top mkd. BATTLE 1935.
--------	---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Point for the 1/4 sec. cor. of sec. 21 only, on the N. bdy. of sec. 27, at midpoint in departure on the S. bdy. of sec. 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, over a plastic-encased magnet, in a supporting mound of stone, 4 ft. base to top, with brass cap mkd. T40N R28E <u>1/4 S21</u> 2025 From this point, the 1/4 sec. cor. of sec. 27 only, bears East, 7.168 chs. dist. From the cor. of secs. 9 and 10 only. WEST, on the S. bdy. of sec. 9. 7.094 The cor. of secs. 16 and 17 only, hereinafter described. 40.000 Point for the 1/4 sec. cor. of sec. 9 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base to top, with brass cap mkd. T40N R28E <u>1/4 S 9</u> 2025 47.094 The 1/4 sec. cor. of sec. 17 only, hereinafter described. 80.000 Point for the cor. of secs. 8 and 9 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E <u>S 8 S 9</u> S17 2025
--------	--

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the 1/4 sec. cor. of secs. 16 and 17, hereinbefore described. NORTH, bet. secs. 16 and 17.
11.30	Base of mountain, bears S. 75° E. and N. 75° W.
41.328	Intersect the S. bdy. of sec. 9. Point for the cor. of secs. 16 and 17 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 6 ft. base to top, with brass cap mkd. T40N R28E S 9 S17 S16 2025 From this point, the cor. of secs. 9 and 10 only, bears East, 7.094 chs. dist. Point for the 1/4 sec. cor. of sec. 16 only, on the S. bdy. of sec. 10, at midpoint in departure on the N. bdy. of sec. 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 6 ft. base to top, with brass cap mkd. T40N R28E 1/4 S16 2025 From this point, the 1/4 sec. cor. of sec. 10 only, bears East, 7.094 chs. dist. From the cor. of secs. 28 and 29 only. West, on the N. bdy. of sec. 29.
7.028	Intersect the E. bdy. of sec. 19. Point for the cor. of secs. 20 and 29 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T40N R28E S19 S20 S29 2025 From this point, the cor. of secs. 19 and 30 only, bears S. 0°40'40" E., 4.349 chs. dist., hereinbefore described. Point for the 1/4 sec. cor. of sec. 20 only, on the N. bdy. of sec. 28, at midpoint in departure on the S. bdy. of sec. 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E 1/4 S20 2025 From this point, the 1/4 sec. cor. of sec. 28 only, bears East, 7.098 chs. dist. From the cor. of secs. 8 and 9 only. N. 00°02'20" W., bet. secs. 8 and 9. 40.000 Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base to top, with brass cap mkd. T40N R28E 1/4 S 8 S 9 2025 80.000 Point for the cor. of secs. 4, 5, 8, and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base to top, with brass cap mkd.
--------	--

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T40N R28E S 5 S 4 S 8 S 9 2025
	N. 00°02'20" W., bet. secs. 4 and 5.
40.000	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 6 ft. base to top, with brass cap mkd. T40N R28E 1/4 S 5 S 4 2025
80.000	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 8 and 9 only. WEST, on the S. bdy. of sec. 8
9.404	The cor. of secs. 17 and 18 only, hereinafter described.
40.000	Point for the 1/4 sec. cor. of sec. 8 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E 1/4 S 8 2025
57.073	The 1/4 sec. cor. of sec. 18 only, hereinafter described.
73.275	The witness point, at the intersection of the Black Rock Desert Wilderness Boundary, with the S. bdy. of sec. 8, hereinafter described.
74.80	Trail road, 12 lks. wide, bears S. 10° E. and N. 10° W.
80.000	Point for the cor. of secs. 7 and 8 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T40N R28E S 7 S 8 S18 2025 From the cor. of secs. 17, 18, 19, and 20, hereinbefore described. N. 00°00'50" W., bet. secs. 17 and 18. 3.00 Top of ridge, bears N. 35° E. and S. 50° W. 40.000 Point for the 1/4 sec. cor. of secs. 17 and 18, determined at 40.00 chs. in latitude from the cor. of secs. 17, 18, 19, and 20, hereinbefore described. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base to top, with brass cap mkd. T40N R28E 1/4 S18 S17 2025 82.482 Intersect the S. bdy. of sec. 8. Point for the cor. of secs. 17 and 18 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 5 ft. base to top, with brass cap mkd. T40N R28E S 8 S18 S17 2025 From this point, the cor. of secs. 8 and 9 only, bears East, 9.404 chs. dist. Point for the 1/4 sec. cor. of sec. 17 only, on the S. bdy. of sec. 9, determined at 40.000 chs. in departure from the corner of 16 and 17 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base to top, with brass cap mkd.
--------	---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T40N R28E 1/4 S17 2025 From this point, the 1/4 sec. cor. of sec. 9 only, bears East, 7.094 chs. dist. From the cor. of secs. 7 and 8 only. WEST, on the S. bdy. of sec. 7. 14.420 Intersect the E. bdy. of sec. 13, T. 40 N., R. 27 E. Point for the cor. of secs. 7 and 18 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T40N T40N R27E S13 T40N S 7 S18 R28E 2025 From this point, the cor. of secs. 12 and 13 only on the E. bdy. of T. 40 N., R. 27 E., bears N. 0°22'20" W., 12.921 chs. dist., hereinbefore described. Point for the 1/4 sec. cor. of sec. 18 only, on the S. bdy. of sec. 8, determined at 37.43 chs. in departure from the cor. of secs. 12 and 13 only, on the E. bdy. of T. 40 N., R. 27 E., hereinbefore described. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E 1/4 S18 2025 From this point, the 1/4 sec. cor. of sec. 8 only, bears East, 17.073 chs. dist.
--------	--

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the cor. of secs. 7 and 8 only. N. 00°03'00" W., bet. secs. 7 and 8.
29.95	Trail road, 15 lks. wide, bears S. 50° E. and N. 50° W.
32.807	A witness point, at the intersection of the Black Rock Desert Wilderness Boundary, with the line bet. secs. 7 and 8, hereinafter described.
40.000	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T40N R28E 1/4 S 7 S 8 2025
74.126	A witness point, at the intersection of the Black Rock Desert Wilderness Boundary, with the line bet. secs. 7 and 8, hereinafter described.
77.20	Trail road, 12 lks. wide, bears N. 30° E. and S. 30° W.
80.000	Point for the cor. of secs. 5, 6, 7, and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T40N R28E S 6 S 5 S 7 S 8 2025
40.000	From the cor. of secs. 4, 5, 8, and 9. WEST, on the line bet. secs. 5 and 8. Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base to top, with brass cap mkd.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS											
	T40N R28E S 5 1/4 — S 8 2025										
77.932	The witness point, at the intersection of the Black Rock Desert Wilderness Boundary, with the line bet. secs. 5 and 8, hereinafter described.										
79.45	Trail road, 15 lks. wide, bears S. 5° E. and N. 5° W.										
80.000	The cor. of secs. 5, 6, 7, and 8.										
	WEST, bet. secs. 6 and 7.										
14.873	Intersect the E. bdy. of sec. 12, T. 40 N., R. 27 E. Point for the cor. of secs. 6 and 7 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.										
	<table><tr><td></td><td>T40N</td></tr><tr><td>T40N</td><td>S 6</td></tr><tr><td>R27E</td><td>—</td></tr><tr><td>S12</td><td>S 7</td></tr><tr><td></td><td>R28E</td></tr></table>		T40N	T40N	S 6	R27E	—	S12	S 7		R28E
	T40N										
T40N	S 6										
R27E	—										
S12	S 7										
	R28E										
	2025										
	From this point, the cor. of secs. 1 and 12 only on the E. bdy. of T. 40 N., R. 27 E., bears N. 0°22'30" W., 17.221 chs. dist., hereinbefore described.										
	Point for the 1/4 sec. cor. of sec. 7 only, on the E. bdy. of sec. 12, T. 40 N., R. 27 E., at midpoint in latitude on the W. bdy. of sec. 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.										
	<table><tr><td>T40N</td></tr><tr><td>R27E R28E</td></tr><tr><td> 1/4 S 7</td></tr></table>	T40N	R27E R28E	1/4 S 7							
T40N											
R27E R28E											
1/4 S 7											
	2025										
	From this point, the 1/4 sec. cor. of sec. 12 only on the E. bdy. of T. 40 N., R. 27 E., bears N. 0°22'50" W., 15.064 chs. dist., hereinbefore described.										

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Point for the 1/4 sec. cor. of sec. 6 only, on the E. bdy. of sec. 1, T. 40 N., R. 27 E., at midpoint in latitude on the W. bdy. of sec. 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T40N R27E R28E 1/4 S 6 2025 From this point, the 1/4 sec. cor. of sec. 1 only on the E. bdy. of T. 40 N., R. 27 E., bears N. 0°22'30" W., 19.379 chs. dist., hereinbefore described. From the cor. of secs. 5, 6, 7 and 8. N. 00°03'00" W., bet. secs. 5 and 6.
3.10	Trail road, 15 lks. wide, bears S. 20° E. and N. 20° W.
7.203	A witness point, at the intersection of the Black Rock Desert Wilderness Boundary, with the line bet. secs. 5 and 6, hereinafter described.
31.280	A witness point, at the intersection of the Black Rock Desert Wilderness Boundary, with the line bet. secs. 5 and 6, hereinafter described.
34.15	Trail road, 15 lks. wide, bears N. 30° E. and S. 30° W.
40.000	Point for the 1/4 sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T40N R28E 1/4 S 6 S 5 2025
70.20	Trail road, 15 lks. wide, bears S. 85° E. and N. 85° W.
71.741	A witness point, at the intersection of the Black Rock Desert Wilderness Boundary, with the line bet. secs. 5 and 6, hereinafter described.
80.000	The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp.

SUBDIVISION OF SECTION 16,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the 1/4 sec. cor. of secs. 16 and 21. N. 00°00'20" E., on the N-S center line of sec. 16.
40.000	Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T40N R28E C 1/4 S16 2025
81.328	The 1/4 sec. cor. of sec. 16 only, on the S. bdy. of sec. 10. From the E. 1/4 sec. cor. of sec. 16 only. WEST, on the E-W center line of sec. 16.
40.000	The center 1/4 sec. cor. of sec. 16.
80.000	The 1/4 sec. cor. of secs. 16 and 17. SUBDIVISION OF SECTION 17, T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA From the 1/4 sec. cor. of secs. 16 and 17. S. 89°11'50" W., on the E-W center line of sec. 17.
82.318	The 1/4 sec. cor. of secs. 17 and 18 SUBDIVISION OF SECTION 18, T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA From the 1/4 sec. cor. of secs. 17 and 18. N. 81°07'30" W., on the E-W center line of sec. 18.
41.997	The witness point, at the intersection of the metes-and-bounds survey of a portion of the Black Rock Desert Wilderness Boundary, with the E-W center line of sec. 18, hereinafter described.
43.65	Trail road, 15 lks. wide, bears S. 5° E. and N. 15° W.
85.872	The 1/4 sec. cor. of secs. 13 and 18 on the W. bdy. of the Tp. hereinbefore described.

SUBDIVISION OF SECTION 20,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the 1/4 sec. cor. of sec. 20 only, on the N. bdy. of sec. 28. N. 0°57'40" E., on the N-S center line of sec. 20.
4.15	Trail road, 15 lks. wide, bears S. 65° E. and N. 65° W.
9.80	Trail road, 15 lks. wide, bears S. 40° E. and N. 45° W.
38.114	Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. T40N R28E C 1/4 S20 2025 from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, for a reference monument, bears S. 45°00' E., 100.0 lks. dist., with brass cap mkd. RM C 1/4 S20 66.0 FT. TO COR. 2025 and an arrow pointing to the corner. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, for a reference monument, bears S. 45°00' W., 200.0 lks. dist., with brass cap mkd. RM C 1/4 S20 132.0 FT. TO COR. 2025 and an arrow pointing to the corner.
58.077	Point for the C-N 1/16 sec. cor. of sec. 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. C N 1/16 S20 C 2025
73.50	Trail road, 15 lks. wide, bears N. 85° E. and S. 85° W.
78.040	The 1/4 sec. cor. of secs. 17 and 20. From the 1/4 sec. cor. of secs. 20 and 21. S. 89°10'30" W., on the E-W center line of sec. 20.

SUBDIVISION OF SECTION 20,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 19.646	Point for the C-E 1/16 sec. cor. of sec. 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{ --- } \text{C} \\ \text{S20} \\ 2025 \end{array}$
39.292	The center 1/4 sec. cor. of sec. 20.
59.55	Trail road, 15 lks. wide, bears S. 10° E. and N. 20° W.
63.30	Trail road, 15 lks. wide, bears S. 60° E. and N. 60° W.
80.304	The 1/4 sec. cor. of secs. 19 and 20.
	From the C-E 1/16 sec. cor. of sec. 20. N. 0°28'50" E., on the N-S center line of the NE1/4 of sec. 20.
19.980	Point for the NE 1/16 sec. cor. of sec. 20 at intersection with the E-W center line of the NE1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. $\begin{array}{c} \text{NE } 1/16 \text{ S20} \\ 2025 \end{array}$
39.960	The E 1/16 sec. cor. of secs. 17 and 20. From the N 1/16 sec. cor. of secs. 20 and 21. S. 89°06'30" W., on the E-W center line of the NE1/4 of sec. 20.
19.478	The NE 1/16 sec. cor. of sec. 20.
38.956	The C-N 1/16 sec. cor. of sec. 20.
	SUBDIVISION OF SECTION 21, T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA From the 1/4 sec. cor. of sec. 21 only, on the N. bdy. of sec. 27. N. 0°00'20" E., on the N-S center line of sec. 21.
78.672	The 1/4 sec. cor. of secs. 16 and 21.

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	MEMORANDUM
	The following metes-and-bounds survey was conducted to delineate a portion of the Black Rock Desert Wilderness Boundary through sections 5, 6, 7, 8, and 18, and was executed utilizing the Black Rock Desert Wilderness Legal Boundary Description, dated May 1, 2026, and the Black Rock Desert Wilderness Map, completed April 15, 2026. Witness points were established at intersections with section lines, and angle points were identified along the boundary, with monumentation specified for key points. From the point for a witness point, on the E-W center line of sec. 18, identical with Boundary Change Point No. 92, shown on the Black Rock Desert Wilderness Map, completed April 15, 2026. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. WP T40N R28E  2025 From this point, the 1/4 sec. cor. of secs. 17 and 18, bears S. 81°07'30" E., 41.997 chs. dist., hereinbefore described. N. 13°20'00" W., on the Black Rock Desert Wilderness Boundary through sec. 18.
1.955	Point for Angle Point No. 1. POINT NOT MONUMENTED
1.652	N. 22°40'00" W., on line 1-2, on the Black Rock Desert Wilderness Boundary through sec. 18. Point for Angle Point No. 2. POINT NOT MONUMENTED
1.697	N. 34°51'00" W., on line 2-3, on the Black Rock Desert Wilderness Boundary through sec. 18. Point for Angle Point No. 3. POINT NOT MONUMENTED

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 39°03'00" W., on line 3-4, on the Black Rock Desert Wilderness Boundary through sec. 18.
1.561	Point for Angle Point No. 4. POINT NOT MONUMENTED _____
	N. 43°54'00" W., on line 4-5, on the Black Rock Desert Wilderness Boundary through sec. 18.
2.652	Point for Angle Point No. 5. POINT NOT MONUMENTED _____
	N. 25°44'00" W., on line 5-6, on the Black Rock Desert Wilderness Boundary through sec. 18.
1.909	Point for Angle Point No. 6. POINT NOT MONUMENTED _____
	N. 32°48'00" W., on line 6-7, on the Black Rock Desert Wilderness Boundary through sec. 18.
1.758	Point for Angle Point No. 7. POINT NOT MONUMENTED _____
	N. 49°01'00" W., on line 7-8, on the Black Rock Desert Wilderness Boundary through sec. 18.
5.636	Point for Angle Point No. 8. POINT NOT MONUMENTED _____
	N. 28°28'00" W., on line 8-9, on the Black Rock Desert Wilderness Boundary through sec. 18.
3.333	Point for Angle Point No. 9. POINT NOT MONUMENTED _____
	N. 39°28'00" W., on line 9-10 on the Black Rock Desert Wilderness Boundary through sec. 18.
4.227	Point for Angle Point No. 10. POINT NOT MONUMENTED _____

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 23°10'00" W., on line 10-11, on the Black Rock Desert Wilderness Boundary through sec. 18.
3.106	Point for Angle Point No. 11. POINT NOT MONUMENTED _____
	N. 24°54'00" W., on line 11-12, on the Black Rock Desert Wilderness Boundary through sec. 18.
4.909	Point for Angle Point No. 12. POINT NOT MONUMENTED _____
	N. 33°23'00" W., on line 12-13, on the Black Rock Desert Wilderness Boundary through sec. 18.
1.515	Point for Angle Point No. 13. POINT NOT MONUMENTED _____
	N. 38°56'00" W., on line 13-14, on the Black Rock Desert Wilderness Boundary through sec. 18.
1.333	Point for Angle Point No. 14. POINT NOT MONUMENTED _____
	N. 35°45'00" W., on line 14-15, on the Black Rock Desert Wilderness Boundary through sec. 18.
1.273	Point for Angle Point No. 15. POINT NOT MONUMENTED _____
	N. 23°30'00" W., on line 15-16, on the Black Rock Desert Wilderness Boundary through sec. 18.
1.515	Point for Angle Point No. 16. POINT NOT MONUMENTED _____
	N. 10°47'00" W., on line 16-17, on the Black Rock Desert Wilderness Boundary through sec. 18.
1.500	Point for Angle Point No. 17. POINT NOT MONUMENTED _____

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 27°25'00" W., on line 17-18, on the Black Rock Desert Wilderness Boundary through sec. 18.
1.212	Point for Angle Point No. 18. POINT NOT MONUMENTED _____
	N. 8°13'00" W., on line 18-19, on the Black Rock Desert Wilderness Boundary through sec. 18.
0.398	Point for a witness point, at intersection of the Black Rock Desert Wilderness Boundary, and the line bet. secs. 8 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. WP T40N R28E S 8 _____ S18 2025 From this point, the cor. of secs. 7 and 8 only, bears WEST, 6.725 chs. dist., hereinbefore described. _____
	N. 8°13'00" W., continue on line 18-19, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.344	Point for Angle Point No. 19. POINT NOT MONUMENTED _____
	N. 0°15'00" W., on line 19-20, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.742	Point for Angle Point No. 20. POINT NOT MONUMENTED _____
	N. 12°20'00" W., on line 20-21, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.606	Point for Angle Point No. 21. POINT NOT MONUMENTED _____

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 28°00'00" W., on line 21-22, on the Black Rock Desert Wilderness Boundary through sec. 8.
2.242	Point for Angle Point No. 22. POINT NOT MONUMENTED _____
	N. 16°42'00" E., on line 22-23, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.788	Point for Angle Point No. 23. POINT NOT MONUMENTED _____
	N. 1°29'00" E., on line 23-24, on the Black Rock Desert Wilderness Boundary through sec. 8.
3.470	Point for Angle Point No. 24. POINT NOT MONUMENTED _____
	N. 2°33'00" W., on line 24-25, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.621	Point for Angle Point No. 25. POINT NOT MONUMENTED _____
	N. 27°52'00" W., on line 25-26, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.288	Point for Angle Point No. 26. POINT NOT MONUMENTED _____
	N. 4°50'00" W., on line 26-27, on the Black Rock Desert Wilderness Boundary through sec. 8.
3.303	Point for Angle Point No. 27. POINT NOT MONUMENTED _____
	N. 33°10'00" W., on line 27-28, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.121	Point for Angle Point No. 28. POINT NOT MONUMENTED _____

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 3°27'00" W., on line 28-29, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.515	Point for Angle Point No. 29. POINT NOT MONUMENTED _____
	N. 8°48'00" E., on line 29-30, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.545	Point for Angle Point No. 30. POINT NOT MONUMENTED _____
	N. 10°41'00" W., on line 30-31, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.303	Point for Angle Point No. 31. POINT NOT MONUMENTED _____
	N. 19°44'00" E., on line 31-32, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.712	Point for Angle Point No. 32. POINT NOT MONUMENTED _____
	N. 17°10'00" W., on line 32-33, on the Black Rock Desert Wilderness Boundary through sec. 8.
0.879	Point for Angle Point No. 33. POINT NOT MONUMENTED _____
	N. 23°36'00" W., on line 33-34, on the Black Rock Desert Wilderness Boundary through sec. 8.
3.636	Point for Angle Point No. 34. POINT NOT MONUMENTED _____
	N. 35°36'00" W., on line 34-35, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.500	Point for Angle Point No. 35. POINT NOT MONUMENTED _____


METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 47°45'00" W., on line 35-36, on the Black Rock Desert Wilderness Boundary through sec. 8.
2.273	Point for Angle Point No. 36. POINT NOT MONUMENTED _____
1.229	N. 19°14'00" W., on line 36-37, on the Black Rock Desert Wilderness Boundary through sec. 8. Point for a witness point, at intersection of the Black Rock Desert Wilderness Boundary, and the line bet. secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. WP T40N R28E S 7 S 8 2025 From this point, the 1/4 sec. cor. of secs. 7 and 8, bears N. 0°03'00" W., 7.193 chs. dist., hereinbefore described. _____ N. 19°14'00" W., continue on line 36-37, on the Black Rock Desert Wilderness Boundary through sec. 7.
0.453	Point for Angle Point No. 37. POINT NOT MONUMENTED _____
1.379	N. 5°49'00" W., on line 37-38, on the Black Rock Desert Wilderness Boundary through sec. 7. Point for Angle Point No. 38. POINT NOT MONUMENTED _____
1.212	N. 32°54'00" W., on line 38-39, on the Black Rock Desert Wilderness Boundary through sec. 7. Point for Angle Point No. 39. POINT NOT MONUMENTED _____

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 3°18'00" E., on line 39-40, on the Black Rock Desert Wilderness Boundary through sec. 7.
3.273	Point for Angle Point No. 40. POINT NOT MONUMENTED _____
	N. 9°53'00" W., on line 40-41, on the Black Rock Desert Wilderness Boundary through sec. 7.
1.576	Point for Angle Point No. 41. POINT NOT MONUMENTED _____
	N. 0°06'00" E., on line 41-42, on the Black Rock Desert Wilderness Boundary through sec. 7.
1.576	Point for Angle Point No. 42. POINT NOT MONUMENTED _____
	N. 16°54'00" W., on line 42-43, on the Black Rock Desert Wilderness Boundary through sec. 7.
1.333	Point for Angle Point No. 43. POINT NOT MONUMENTED _____
	N. 0°13'00" W., on line 43-44, on the Black Rock Desert Wilderness Boundary through sec. 7.
14.273	Point for Angle Point No. 44. POINT NOT MONUMENTED _____
	N. 15°34'00" W., on line 44-45, on the Black Rock Desert Wilderness Boundary through sec. 7.
4.273	Point for Angle Point No. 45. POINT NOT MONUMENTED _____
	N. 0°46'00" W., on line 45-46, on the Black Rock Desert Wilderness Boundary through sec. 7.
3.288	Point for Angle Point No. 46. POINT NOT MONUMENTED _____

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 13°19'00" W., on line 46-47, on the Black Rock Desert Wilderness Boundary through sec. 7.
2.379	Point for Angle Point No. 47. POINT NOT MONUMENTED _____
	N. 9°43'00" E., on line 47-48, on the Black Rock Desert Wilderness Boundary through sec. 7.
1.318	Point for Angle Point No. 48. POINT NOT MONUMENTED _____
	N. 22°29'00" E., on line 48-49, on the Black Rock Desert Wilderness Boundary through sec. 7.
1.439	Point for Angle Point No. 49. POINT NOT MONUMENTED _____
	N. 29°38'00" E., on line 49-50, on the Black Rock Desert Wilderness Boundary through sec. 7.
4.850	Point for a witness point, at intersection of the Black Rock Desert Wilderness Boundary, and the line bet. secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. WP T40N R28E S 8 S 7  2025 From this point, the cor. of secs. 5, 6, 7, and 8, bears N. 0°03'00" W., 5.874 chs. dist., hereinbefore described. _____
	N. 29°38'00" E., continue on line 49-50, on the Black Rock Desert Wilderness Boundary through sec. 8.
3.271	Point for Angle Point No. 50. POINT NOT MONUMENTED _____


METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 16°15'00" E., on line 50-51, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.909	Point for Angle Point No. 51. POINT NOT MONUMENTED _____
	N. 4°18'00" W., on line 51-52, on the Black Rock Desert Wilderness Boundary through sec. 8.
1.199	Point for a witness point, at intersection of the Black Rock Desert Wilderness Boundary, and the line bet. secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. WP T40N R28E S 5 _____ S 8 2025 From this point, the cor. of secs. 5, 6, 7, and 8, bears WEST, 2.068 chs. dist., hereinbefore described. _____
	N. 4°18'00" W., continue on line 51-52, on the Black Rock Desert Wilderness Boundary through sec. 5.
2.437	Point for Angle Point No. 52. POINT NOT MONUMENTED _____
	N. 21°37'00" W., on line 52-53, on the Black Rock Desert Wilderness Boundary through sec. 5.
5.132	Point for a witness point, at intersection of the Black Rock Desert Wilderness Boundary, and the line bet. secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. WP T40N R28E S 6 S 5 2025 From this point, the cor. of secs. 5, 6, 7, and 8, bears S. 0°03'00" E., 7.203 chs. dist., hereinbefore described. _____

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 21°37'00" W., continue on line 52-53, on the Black Rock Desert Wilderness Boundary through sec. 6.
3.535	Point for Angle Point No. 53. POINT NOT MONUMENTED _____
	N. 1°16'00" E., on line 53-54, on the Black Rock Desert Wilderness Boundary through sec. 6.
8.303	Point for Angle Point No. 54. POINT NOT MONUMENTED _____
	N. 13°19'00" W., on line 54-55, on the Black Rock Desert Wilderness Boundary through sec. 6.
1.788	Point for Angle Point No. 55. POINT NOT MONUMENTED _____
	N. 43°35'00" W., on line 55-56, on the Black Rock Desert Wilderness Boundary through sec. 6.
2.121	Point for Angle Point No. 56. POINT NOT MONUMENTED _____
	N. 3°46'00" E., on line 56-57, on the Black Rock Desert Wilderness Boundary through sec. 6.
4.106	Point for Angle Point No. 57. POINT NOT MONUMENTED _____
	N. 14°21'00" E., on line 57-58, on the Black Rock Desert Wilderness Boundary through sec. 6.
1.364	Point for Angle Point No. 58. POINT NOT MONUMENTED _____
	N. 31°54'00" E., on line 58-59, on the Black Rock Desert Wilderness Boundary through sec. 6.
4.472	Point for a witness point, at intersection of the Black Rock Desert Wilderness Boundary, and the line bet. secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	WP T40N R28E S 5 S 6  2025 From this point, the 1/4 sec. cor. of secs. 5 and 6, bears N. 0°03'00" W., 8.720 chs. dist., hereinbefore described.
25.588	N. 31°54'00" E., continue on line 58-59, on the Black Rock Desert Wilderness Boundary through sec. 5. Point for Angle Point No. 59. POINT NOT MONUMENTED
1.409	N. 26°26'00" E., on line 59-60, on the Black Rock Desert Wilderness Boundary through sec. 5. Point for Angle Point No. 60. POINT NOT MONUMENTED
1.061	N. 8°28'00" W., on line 60-61, on the Black Rock Desert Wilderness Boundary through sec. 5. Point for Angle Point No. 61. POINT NOT MONUMENTED
0.773	N. 20°19'00" W., on line 61-62, on the Black Rock Desert Wilderness Boundary through sec. 5. Angle Point No. 62, identical with Boundary Change Point No. 93, shown on the Black Rock Desert Wilderness Map, completed April 15, 2026, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. BRDW N74461 2021, with a black iron pipe, 3 ins. diam., firmly set, projecting 42 ins. above the ground, alongside stainless steel post. Point is located in the center of a closed trail road, 12 lks. wide, bears N. 35° E. and S. 35° W.

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 20°23'00" W., on line 62-63, on the Black Rock Desert Wilderness Boundary through sec. 5.
1.000	Point for Angle Point No. 63. POINT NOT MONUMENTED _____
	N. 36°57'00" W., on line 63-64, on the Black Rock Desert Wilderness Boundary through sec. 5.
5.727	Point for Angle Point No. 64. POINT NOT MONUMENTED _____
	N. 21°24'00" W., on line 64-65, on the Black Rock Desert Wilderness Boundary through sec. 5.
4.879	Point for Angle Point No. 65. POINT NOT MONUMENTED _____
	N. 31°47'00" W., on line 65-66, on the Black Rock Desert Wilderness Boundary through sec. 5.
3.561	Point for Angle Point No. 66. POINT NOT MONUMENTED _____
	N. 32°07'00" W., on line 66-67, on the Black Rock Desert Wilderness Boundary through sec. 5.
0.848	Angle Point No. 67, identical with Boundary Change Point No. 94, shown on the Black Rock Desert Wilderness Map, completed April 15, 2026, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. BRDW N74461 2021, with a black iron pipe, 3 ins. diam., firmly set, projecting 48 ins. above the ground, alongside stainless steel post. Change the brass cap mks. 2021 to 2025. Point is located in the center of a closed trail road, 12 lks. wide, bears S. 85° E. and N. 85° W. _____
	N. 51°43'00" W., on line 67-68, on the Black Rock Desert Wilderness Boundary through sec. 5.
1.288	Point for Angle Point No. 68. POINT NOT MONUMENTED _____

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 62°35'00" W., on line 68-69, on the Black Rock Desert Wilderness Boundary through sec. 5.
1.864	Point for Angle Point No. 69. POINT NOT MONUMENTED
	N. 85°44'00" W., on line 69-70, on the Black Rock Desert Wilderness Boundary through sec. 5.
3.201	Point for a witness point, at intersection of the Black Rock Desert Wilderness Boundary, and the line bet. secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. WP T40N R28E  2025 From this point, the cor. of secs. 5, 6, 31, and 32 on the N. bdy. of the Tp., bears N. 0°03'00" W., 8.259 chs. dist., hereinbefore described.
	N. 85°44'00" W., continue on line 69-70, on the Black Rock Desert Wilderness Boundary through sec. 6.
10.663	Point for Angle Point No. 70. POINT NOT MONUMENTED
	N. 87°28'00" W., on line 70-71, on the Black Rock Desert Wilderness Boundary through sec. 6.
3.045	Point for Angle Point No. 71. POINT NOT MONUMENTED
	N. 86°08'00" W., on the Black Rock Desert Wilderness Boundary through sec. 6.
1.606	A witness point on the E. bdy. of Sec. 1, T. 40 N., R. 27 E., identical with Boundary Change Point No. 95, shown on the Black Rock Desert Wilderness Map, completed April 15, 2026, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. BRDW N74461 2021.

METES-AND-BOUNDS SURVEY OF A PORTION OF THE BLACK ROCK DESERT
WILDERNESS BOUNDARY THROUGH SECS. 5, 6, 7, 8, AND 18,
T. 40 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From this point, the cor. of secs. 6 and 31 on the N. bdy. of the Tp., bears N. 0°22'30" W., 7.222 chs. dist., hereinbefore described.

GENERAL DESCRIPTION

The land in the surveyed area contains rolling hills and mountainous terrain in the north and south areas with level land on the east and west areas of the survey, ranging in elevation from approximately 4000 to 5200 ft. The drainage is generally to the south.

The soil varies from sandy alkali flats to volcanic and rocky in the hills and higher elevations.

There is no timber in the area surveyed.

Three hot springs were located in the surveyed area. West Pinto Hot spring is located within section 19 and two of the heads of Pinto Hot Springs are located within section 17.

There are no settlers in the area surveyed.

Geothermal exploration is being conducted in the western portion of the area surveyed.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Richard J. Diekmann	Cadastral Surveyor
Robert S. Hollis	Survey Technician
Lance W. Smith	Nevada Professional Land Surveyor (Experienced Services Program)

CERTIFICATE OF SURVEY

I, Kelly R. Totten, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing the date of the 12th day of August, 2025, I have dependently resurveyed a portion of the east boundary of Township 40 North, Range 27 East, and dependently resurveyed a portion of the subdivisional lines, surveyed portions of the east and north boundaries and a portion of the subdivisional lines, and subdivided sections 16, 17, 18, 20, and 21, and executed a metes-and-bounds survey of a portion of the Black Rock Desert Wilderness Boundary through sections 5, 6, 7, 8, and 18, Township 40 North, Range 28 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said surveys have been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUN 30 2026

(Date)


(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the east boundary of Township 40 North, Range 27 East, and the dependent resurvey of a portion of the subdivisional lines, the survey of portions of the east and north boundaries and a portion of the subdivisional lines, the subdivision of sections 16, 17, 18, 20, and 21, and a metes-and-bounds survey of a portion of the Black Rock Desert Wilderness Boundary through sections 5, 6, 7, 8, and 18, Township 40 North, Range 28 East, of the Mount Diablo Meridian, Nevada, executed by Kelly R. Totten, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUL 02 2026

(Date)


(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Townships 40 North, Ranges 27 and 28 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~