

Subdivision of frac. T. 27 N., R. 22 E.

Chains

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

43.60 Foot of descent. Dry drain, course S. 60° W. Begin ascent.

46.50 Top of ascent. South point of ridge, brs. N. Begin descent.

47.30 Foot of descent. Dry drain, course S, 20° W. Begin ascent.

69.00 Top of ascent. Ridge, brs. N. and S. Begin descent.

80.04 The cor. of secs. 4, 5, 8 and 9.

Land, mountainous, - grazing.
Soil, rocky and sandy, 3rd rate.
No timber.

N. $0^{\circ} 03'$ W. on a true line bet. secs. 4 and 5.

Over mountainous land, ascending along W. slope of rocky and broken ridge.

14.00 Dry drain, course N. 80° W.

21.00 Low ridge, brs. E. and W.

23.00 Dry drain, course S. 80° W.

27.40 Top of ascent. Ridge, brs. E. and W. Begin descent.

36.00 Foot of descent. Dry drain, course S. 60° W. Begin ascent.

40.00 Set an iron post for the $\frac{1}{4}$ sec. cor. bet. secs. 4 and 5, with brass cap stamped

$\frac{1}{4}$ S 5 in W. half
S 4 in E. half
1912 in S.

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

53.00 Top of ascent. Ridge, brs. N. 60° W. and S. 60° E. Begin descent.

63.90 Foot of descent. Dry draw, course N. 45° W. Begin ascent.

65.93 Intersect the N. bdy. of Tp., at a point from which the cor. of secs. 4, 5, 32 and 33, Tps. 27 and 28 N., R. 22 E. brs. West, 5.22 chs. dist.

Set an iron post for C.C. of frac. secs. 4 and 5, with