

Subdivision of T. 28 N. R. 22 E.

Chains

Build a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling, - grazing.

Soil, stony and sandy, 3rd rate.

From the cor. of secs. 11, 12, 13 and 14, I run

East on a true line bet. secs. 12 and 13.

Over rolling land.

- 40.00 Set an iron post 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. bet. secs.
12 and 13, with brass cap stamped

$\frac{1}{4}$ S 12 in N. half
S 13 in S. half

Dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist., and raise
a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

- 59.77 Intersect the Reservation bdy. 14.52 chs. N. $32^{\circ} 02'$ W. of the $54\frac{1}{2}$
Mil. Post.

Set an iron post 26 ins. in the ground, for C.C. of secs. 12 and 13,
with brass cap stamped

C C in W. edge
T 28 N S 13 in SW. quadrant
R 22 E S 12 in NW. quadrant
P L I R in middle
4 notches on S. and 2 notches on N. edge

Build a mound of stone, 4 ft. base, 2 ft. high, W. of cor.

Land, gently rolling - grazing.

Soil, sandy and stony, 3rd rate.

From the cor. of secs. 11, 12, 13 and 14, I run

N. $0^{\circ} 01'$ W. bet. secs. 11 and 12.

Over gently rolling land.

- 15.00 Dim road, hrs. E. and W.

- 40.00 Set an iron post 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. bet. secs.
11 and 12, with brass cap stamped

$\frac{1}{4}$ S 11 in W. half
S 12 in E. half

Dig pits 18x18x12 ins. N. and S. of cor. 3 ft. dist., and raise a
mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

- 80.00 Set an iron post 26 ins. in the ground, for the cor. of secs. 1,
2, 11 and 12, with brass cap stamped