

N. B., T. 26 N., R. 64 E., Mt. D. M.

Chains.

st.

North on a true line between sections 1-6.

Va. $16^{\circ}30'$ East.

Ascend.

17.70

Top of Ridge, bears N. $63\frac{1}{2}^{\circ}$ E. N. $63\frac{1}{2}^{\circ}$ W. and descend.

36.00

Cross Gulch, 4 lks. wide, Course N. 65° E. and ascend.

40.00

Set a lime stone $30 \times 18 \times 6$ ins., 15 ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face, and raised a mound of stone. Pits impracticable.

from which

A Juniper 18 ins. diam. bears S. 31° E. 48 lks. dist. marked $\frac{1}{4}$ S. B. T.

A Juniper 16 ins. diam. bears S. $62\frac{1}{4}^{\circ}$ W. 56 lks. dist. marked $\frac{1}{4}$ S. B. T.

60.00

Top of Ridge, bears S. 70° W. N. 70° E. and descend.

80.00

Set a lime stone $36 \times 14 \times 10$ ins. 37 ins. in the ground, for Cor. to Tps. 26 and 27 N. R's 63. and 64 E., marked with 6 notches on each edge, and raised a mound of stone. Pits impracticable.

from which

A Pine 34 ins. diam. bears N. $86\frac{1}{2}^{\circ}$ W. 16 lks. dist. marked T. 26 N. R. 63 E., S., 31 B. T.