

58 West boundary of ^{16²}
 Township 16 NORTH Range 51 EAST
 Monte Diablo Base and Meridian.

Standard
 From the Cor. to tps. 16 — N. Rs. 50 & 51 E.

Run. North between sections 31 & 30

Variation 17° East.

Descend 9° slope

5.70 Ravine about 40 feet deep, course West and ascend 13° slope

6.00 Top of spur beam NW and descend 10° slope

17.00 Over nearly level ground Leave scattering timber beam NE & SW

40.00 Set a post 3 ft. long, 3 ins. diam. with marked stone

12 ins. in the ground, for $\frac{1}{2}$ Sec. Cor., marked $\frac{1}{2}$ S. on

W face, dug pits, 18 x 18 x 12 ins., N and S of
 post 5½ ft. dist., and raised a mound of earth 1½ ft.
 high, 3½ ft. base, around post.

50.70 Cross Road, bears, E & W

70.00 Dry Channel 30 lks. wide, course NW

80.00 Set a Sioux stone 22 x 14 x 12 ins. 16 ins. in
 the ground for Cor. to Secs. 25, 30, 31 & 30 marked
 with / notch on S. and 5 notches on N. edges and
 dug pits, 18 x 18 x 12 ins. in each Sec., 5½ ft. dist.,
 and raised a mound of earth 2 ft. high, 4½ ft. base
 alongside

The necessary corrections corresponding
 to the given slope & has been applied and
 the corner & located according to the true
 distance thus obtained.

South 17.00 chs Mountainous
 North 63.00 chs Level
 Whitt fence
 Soil 1 acre