

Duts J. 18N. R 23E.

No 12'E on a random line
But sees. 1 and 2 Over Ms

4000 Set temp 1/4 sec ~~85° 33' W 48~~
7715 Set N Bdy of Sp ~~43' W of~~
~~the from~~ Er sees 35 and 36. As this

falling is out of limits from
North and 5 line I retroce S. Bdy
~~See 34. See Resurvey~~

At point of intersection I set
Basalt stone 16 x 12 x 6 ^{ms} firmly in
a mound of stone for clearing corner
sees 1 and 2. Marked with +
1 ^{groove} notch on the E and 5 ^{grooves} notches on
the W ~~face~~ C.C. on S face
from which bears a

Cedar 5 ^{ms} diam S 23° 30' W 86 lbs dist
Marked T 18N R 23E S 1 B.T.

Cedar 6 ^{ms} diam S 1° E 128 lbs dist

Thence 5 ^{ms} mowed on a line
Marked on 18N R 23E S 1 B.T.
S 0° 12' W ¹ But sees 1 and 2

21.00 Reverse Course Rk.

29.00 Spur of ridge slopes E descend

37.15 Set a granite stone 13 x 8 x 6 ^{ms} firmly in a mound of stone
for 1/4 sec cor. Marked 1/4 on the
W face. Raise a mound of stone
3 ft base and 2 ft high W of cor