

THIRD STANDARD PARALLEL SOUTH, through RANGE 50 EAST.

CHAINS

80.00 Set a basalt stone, 15x10x6 ins., 10 ins. in the ground, for standard cor. of secs. 35 and 36, marked S C on N., with 1 groove on E. and 5 grooves on W. faces, and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Pits impracticable.

Land, rolling.

Soil, sandy, 3rd. rate.

No timber; undergrowth, greasewood.

Dense undergrowth on 80.00 chs.

East, on S. bdy. of sec. 36.

Ascend over rolling and sandy land, through dense undergrowth.

11.00 Wash, 2.00 chs. wide, 25 ft. deep, course SW.

21.00 Wash, 1.75 chs. wide, 25 ft. deep, course SW.

28.50 Wash, 1.00 ch. , wide, course SW.

35.00 Wash, 1.00 ch. , wide, course SW.

Difference between measurement of 40.00 chs., by two sets of chainmen is 18 lks., position of middle point

By 1st. set, 40.09 chs.,

By 2nd. set, 39.91 chs., the mean of which is

40.00 Set a basalt stone, 15x9x6 ins., 10 ins. in the ground, for standard ¼ sec. cor., marked S C ¼ on N. face, and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Pits impracticable.

48.00 Wash, 2.00 chs. wide, 20 ft. deep, course SW.

60.00 Wash, 2.00 chs. wide, 15 ft. deep, course SW.

79.00 Wash, 2.50 chs. wide, 20 ft. deep, course SW.

Difference between measurement of 80.00 chs., by two sets of chainmen is 20 lks., position of middle point

By 1st. set, 80.10 chs.,

By 2nd. set, 79.90 chs., the mean of which is

80.00 Set a limestone, 15x12x6 ins., 10 ins. in the ground, for standard cor. of Tps. 12 S., Rs. 50 and 51 E., marked SCL2S on N., 50E on W. and 51 E on E. faces, with 6 grooves on N., E.