

Subdivision of T 25 N, R 64 E.

Chains.

- cor.; dig pits 18/18/12 ins. E. and W. of cor. 4 ft. dist. and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high over deposit.
- In E. pit drive a juniper stake 2 ft. long, 2 ins. sq. 12 ins. in the ground, marked $\frac{1}{4}$ S 3 on the N. face and 10 on the S. face.
- 80.08 The cor. of secs. 3, 4, 9 and 10.
Land, level.
Soil, adobe and loam. 1st. rate.
sagebrush and chico. No timber.
-
- N $0^{\circ}02'W$ bet. secs. 3 and 4.
Over level land.
- 40.00 Deposit a marked stone 12 ins. in the ground for $\frac{1}{4}$ sec cor.; dig pits 18/18/12 ins. N. and S. of cor. 4 ft. dist. and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high over deposit.
- In S. pit drive a juniper stake 2 ft. long, 2 ins. sq. 12 ins. in the ground, marked $\frac{1}{4}$ S 4 on the W. face and 3 on the E. face.
- 79.90 Slough, bears N.E. and S.W.
- 99.89 Intersect the 5th. Standard Parallel North at N $89^{\circ}48'W$ 1.13 chs. from the standard cor. of secs. 34 and 35 re-established by me July, 23, 1909.
- Set a limestone 15/9/4 ins., 10 ins. in the ground for closing cor. to secs. 3 and 4, marked C C on S. with 3 grooves on E. and 3 grooves on W. face; dig pits 24/18/12 ins. crosswise on each line, E. and W. 3 ft. and S. of stone 7 ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high S. of cor.
- Land, level.
- Soil, adobe and loam. 1st. rate.
- Sagebrush, greasewood and grass land. No timber.

July 30, 1909.