

Resurvey of N. bdy. of T 28N., R. 31E.

chains

and raise a mound of stone
2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

From this cor. I resurvey.

W. est. bet. secs. 1 and 36.

Over rolling land; ascend.

34.19

Wash, 30 lbs. wide, course S. 30° E.

40.00

Intersect the old $\frac{1}{4}$ sec. cor. of secs.
1 and 36, which is a post $2\frac{1}{2} \times 4 \times 4$ ft.
above ground, marked $\frac{1}{4}$ 5, witnessed
by pits and mound of earth. I
destroy all trace of the old cor. and
reestablish it at the same point
as follows.

Set an iron post 3 ft. long,
1 in. diam., 24 ins. in the
ground for $\frac{1}{4}$ cor. of secs. 1 and
36, with brass cap mkd.;

$$\begin{array}{r} 536 \\ \frac{1}{4} \\ \hline 51 \end{array}$$

51

1912

and raise a mound of stone,
2 ft. base $1\frac{1}{2}$ ft. high, N. of cor.

42.09

Wash, 20 lbs. wide, course S. 45° E.

74.39

Wash, 50 lbs. wide, course S. 40° E.

80.00

The cor. of secs. 1, 2, 35 and 36

land, rolling.

Soil, stony, 2nd rate

undergrowth, sage brush.

No timber

Survey of S. bdy. of T 29N., R. 31E.

From the cor. of secs. 1, 2, 35 and 36

I run west on true line to S.

bdy. of sec. 35.

Over rolling land; ascend.

12.00

Top of round hill.

27.20

Top of ridge, bears S. 30° E. and N. 30° W.
; descend.

40.00

Set an iron post 3 ft. long,
1 in. diam., 24 ins. in the