

Subdivision of T. 28 N., R. 31 E.

Chains 1 in. diam., 24 ins. in the ground for $\frac{1}{4}$ cor. of sec. 2, with brass cap mk'd;

52 $\frac{1}{4}$

1912

and raise a mound of stone, 2 ft. base 1 $\frac{1}{2}$ ft. high, E. of cor.

42.70 Set an iron post 3 ft. long, 1 in. diam., 24 ins. in the ground for $\frac{1}{4}$ cor. of sec. 3, with brass cap mk'd;

53 $\frac{1}{4}$

1912

and raise a mound of stone, 2 ft. base 1 $\frac{1}{2}$ ft. high W. of cor.

43.00 Top of ridge, bears N. 80° E. and S. 80° W.; descend.

48.00 Ascend.

74.00 Top of ridge, bears N. 75° E. and S. 75° W.; descend.

80.12 I intersect N. ldy of Sp. 1.67 Chs W. of cor. of secs. 34 and 35 of T. 29 N., R. 31 E. At the point of intersection I build a cor. as follows:-

Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground for closing cor. of secs. 2 and 3, with brass cap mk'd;

T 29 N. R. 31 E.

CC. 534 | 535

53 | 52

T. 28 N.

1912

and raise a mound of stone, 2 ft. base 1 $\frac{1}{2}$ ft. high S. of cor. Land rolling.