

Subdivision of T. 29 N., R. 31 E.

Chains. Aug. 7.
Went on a true line bet. secs. 19 and 30.
Over rough mountainous land; ascend
8.00 Top of ridge, bearing S. 30° W. and
and N. 30° E.; descend.
13.00 Cross wash, 20 lbs. wide course
S. 30° W.; ascend.
21.00 Top of spur, bears S. 45° E and
N. 45° W.; descend.
29.00 Gulch. course S. 45° E.; ascend.
40.00 Set an iron post 3 ft. long,
1 in. diam., 24 ins. in the
ground for $\frac{1}{4}$ cor. of secs. 19 and
30 with brass cap mked.;

519
1
4

530

1912

and raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
47.00 Top of spur, bears S. 60° E. and
N. 60° W.; descend.
78.00 Canyon, 20 lbs. wide, course S. 60° E
; ascend

85.73 Intersect W. bdy. of T. 5.90 Chains
N. of $\frac{1}{4}$ cor. of sec. 25, T. 29 N., R. 30 E.
hereinafter described. At the
point of intersection I build
a cor. as follows:

Set an iron post 3 ft. long,
2 ins. diam., 24 ins. in the
ground for closing cor. of secs.
19 and 30 with brass cap mked.;

T 29 N.

R 30 E R 31 E

CC 519
S 25 $\frac{1}{4}$ 530
1912

and raise a mound of stone,
2 ft. base $1\frac{1}{2}$ ft. high E. of cor.
Sand mound arising
Soil rocky, 3 d rate