

DEPENDENT RESURVEY WEST BOUNDARY T. 16 S., RANGE 50 EAST.

CHAINS

the ground, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with
brass cap mkd:

S 36 $\frac{1}{4}$
|
1921

40.59 dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.
At proportionate distance, set an iron post, 3 ft. long,
1 in. diam., 26 ins. in the ground, for the restored
 $\frac{1}{4}$ sec. cor. of sec. 31 only, with brass cap mkd:

$\frac{1}{4}$ S 31
|
1921

50.80 and raise a mound of stone, 2 ft. base, 1 $\frac{3}{4}$ ft. high,
81.19 E. of cor.
Road bears NE. and SW.
The restored cor. of Tp. 16 S., Rs. 49 and 50 E., here-
inbefore described.

Land, level.

Soil, sandy and gravelly to rocky; 2nd to 3rd rate.

Undergrowth, creosote brush, shad scale, greasewood.

No timber.

SURVEY OF THE RANGE LINE IN T. 16 S. BET. Rs. 48 & 49 E.

From the Std. cor. of T. 16 S., Rs. 48 and 49 E., here-
inbefore described,

North, on true line, bet. secs. 31 and 36,

Over level land thru dense undergrowth.

53.20 At a point 440 chs. southing from the NE. cor. of the Tp.
16 S., R. 49 E., set an iron post, 3 ft. long, 1 in
diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs.
31 and 36, with brass cap mkd:

$\frac{1}{4}$
S 36 | S 31
|
1921

dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.