

Dependent Resurvey of the E. Bdy. of T. 4 N., R. 67 E.

Chains.

Alongside the cor. of Ts. 3 and 4 N., Rs. 67 and 68 E., which is a granite stone, firmly set, 10 x 10 x 4 ins. above ground, mkd. 6 grooves on N., S., E. and W. faces, from which

A juniper, 10 ins. in diam., bears N. $57\frac{1}{2}^{\circ}$ E., 100 lks. dist., mkd. T4N R68E S31 BT

A juniper, 6 ins. in diam., bears S. 77° E., 127 lks. dist., mkd. T3N R68E S6 BT

A juniper 12 ins. in diam., bears S. $34\frac{1}{2}^{\circ}$ W., 147 lks. dist., mkd. T3N R67E S1 BT

A juniper 12 ins. in diam., bears N. 19° W., 62 lks. dist., mkd. T4N R67E S36 BT

set an iron post, 3 ft. long, 3 ins. in dia., 27 ins. in the ground, for the cor. of Ts. 3 and 4 N., Rs. 67 and 68 E., with brass cap mkd.

T4N
R67E R68E
S36 S31
S1 S6
T3N
1923

N. $0^{\circ} 09'$ W., on a true line, bet. secs. 31 and 36.

Asc. gradual SW. slope over slightly rolling land, through dense juniper and pinon pine timbered.

40.04. Intersect the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, which is a granite stone, 12 x 12 x 6 ins. above ground, mkd. $\frac{1}{4}$ on W. face, from which

A juniper, 8 ins. in diam., bears S. $88\frac{1}{2}^{\circ}$ E., 83 lks. dist., mkd. $\frac{1}{4}$ S31 BT

A juniper, 6 ins. in diam., bears N. 61° W., 56 lks. dist., mkd. $\frac{1}{4}$ S36 BT

Alongside, set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S36 S31
1923

Asc. SW. slope 230 ft.