Dependent Resurvey

14 of a Portion of the West Boundary of T. 44 N., R. 30 E.

Chains

From The cor. of secs. 7, 12, 13 and 18, on W. bdy. T. 44 N., R. 30 E. heretofore described and referring to Rs. 29 and 30 E., I now change to a cor. common to secs. 7 and 18, R. 30 E. only, with brass cap mkd.

T44N | T44N
R29E | S 7
S36 | S18
| R30E
1921

Raise the mound of stone, 2 ft. base 1½ ft. high, E. of cor. Destroyed the mound of stone W. of cor.

South on W. Bdy. sec. 18.

17.29 The cor. of Ts. 43 and 44 N., R. 29 E., heretofore described.

40.00 Intersect the ¼ cor. of secs. 13 and 18, which is an iron post, 1 ins dia., 24 ins. above the ground, surrounded by a mound of stone, mkd. and witnessed as described by the surveyor general. I now change the markings on brass cap so a to refer to sec. 18 only, as follows:

¼ S 18
1921

Raise a mound of stone, 2 ft. base, 1½ ft. high, E. of cor. Destroyed the mound of stone W. of cor.

From the cor. of secs. 7 and 18, heretofore referred to North, on W. Bdy. of sec. 7.

40.00 Intersect the ¼ cor. of secs. 7 and 12, which is an iron post post, 1 in. dia., 24 ins. above the ground, surrounded by a mound of stone, mkd. and witnessed as described by the surveyor general. I now change the markings on brass cap so as to refer to sec. 7 only as follows:

¼ S 7
1921

Raise a mound of stone, 2 ft. base, 1½ ft. high, E. of cor.

79.92 Intersect the cor. of secs. 1, 6, 7 and 12, which is an iron post, 2 ins. dia., 20 ins. above the ground, surrounded by a mound of stone, mkd. and witnessed as des-