

Survey of a portion of the subdivisions of T. 46 N., R. 31 E.

Chains.

secs. 17 and 18.

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the closing cor. of secs. 7 and 8, with brass cap mkd.

C | C
T46N | R31E
S7 | S8
S17
1923

Deposit a granite stone, 9 x 8 x 4 ins., with cross marked (x), at base of post.

Land, slightly rolling. Soil, sandy and rocky.

Undergrowth, medium growth of sage and scattering bunch grass.

From the cor. of secs. 5, 6, 7 and 8,

N. 0° 04' W., on a true line, bet. secs. 5 and 6.

Desc. NW. slope over rolling land.

23.50 Dry wash, 30 ft. below sec. cor., course W.

31.80 Dry wash, 30 ft. below wash, course SW. Asc. SW. slope 70 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S6 | S5
1923

Deposit a granite stone, 9 x 6 x 2 ins., with cross marked (x), at base of post.

43.30 Slope changes to NW., 30 ft. above sec. cor.

Desc. 20 ft. to

52.00 Dry wash, course SW. Asc. SW. slope 100 ft. to

91.29 Intersect the S. Bdy. of T. 47 N., R. 31 E., at a point, S. 88° 34' E., 2.21 chs. dist., from the cor. of secs. 31 and 32, which is an iron post, 2 ins. in dia., firmly set and properly marked and witnessed, as described in the field notes of T. 47 N., R. 31 E.

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the closing cor. of secs. 5 and 6,