

Survey of a portion of the subdivisions of T. 47 N., R. 31 E.

Chains.	deposit a stone with cross marked (x) at base of post, for the $\frac{1}{4}$ sec. cor. for sec. 1, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S1 \mid \\ 1922 \end{array}$
	From the cor. of secs. 1 and 2, 11 and 12, North, on a sectional guide meridian, bet. secs. 1 and 2. Desc. N.W. slope over rough mountainous land.
14.00	Dry wash, 250 ft. below sec. cor., course N. 70° W. Asc. S.W. slope.
19.40	Top of spur, 20 ft. above wash, projects W. Desc. N.W. slope.
20.20	Dry wash, 20 ft. below spur, course S.W. Asc. S.W. slope.
36.20	Top of spur-ridge, 240 ft. above wash, bears E. and W. Desc. N.W. slope 50 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 20 ins. in the ground, to solid rock, in a mound of stone, and deposit a stone with cross marked (x) at base of post, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S2 \mid S1 \\ 1922 \end{array}$
47.00	Dry wash, 110 ft. below $\frac{1}{4}$ sec. cor., course N.W. Asc. S.W. slope.
65.00	Top of spur, 370 ft. above wash, projects W. Desc. N.W. slope.
79.00	Head of dry wash, 240 ft. below spur, course N. 70° W. Asc. S.W. slope.
97.00	Top of ridge, 60 ft. above wash, bears N.W. and S.E. Desc. N.E. slope
110.00	Top of spur, 150 ft. below ridge, projects N.E. Desc. N. slope 220 ft. to
115.56	Intersect the Nevada-Oregon State Line, at a point, S. 89° 17' W., 25.96 chs. dist. from the 226th Mile Post.