

Survey of the N. Bdy. of T. 14 N., R. 50 E.

Chains. From the cor. of Ts. 14 and 15 N., Rs. 50 and 51 E., which is an iron post, 3 ins. in diam., firmly set, properly marked and witnessed, as described in the field notes of T. 14 N., R. 51 E.,

West, on a random line, on the N. Bdy. of T. 14 N., R.

50 E., setting temporary points at 40.00 and 80.00 chs.

477.37 Fall 28 lks. S. of the cor. of Ts. 14 and 15 N., Rs. 49 and 50 E., hereinbefore described.

Thence

S. $89^{\circ} 58'$ E., on a true line, bet. secs. 6 and 31, on the N. Bdy. of the township.

Desc. 50 ft. over N. slope, over rolling mountainous land.

4.80 Dry wash, drains S. 85° E. Asc. SW. slope 120 ft. to top of spur.

5.70 Dim road, bears NW. and S. 85° E.

17.30 Top of spur, projects S. Desc. SE. slope 140 ft. through medium to dense growth of pinon pine and juniper.

35.50 Dry wash, drains S. Asc. W. slope 30 ft.

37.37 Set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in the ground, to solid rock, in a mound of stone 26 ins. high, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S31

S6
1926

from which

A pinon pine 10 ins. in diam., bears N. $62\frac{1}{2}^{\circ}$ E., 43 lks. distant, marked $\frac{1}{4}$ S31 BT

A pinon pine 9 ins. in diam., bears S. 51° W., 20 lks. distant, marked $\frac{1}{4}$ S6 BT

Asc. W. slope 20 ft.

42.20 Top of spur, projects S. Desc. E. slope 30 ft.

44.20 Dry wash, drains S. Asc. W. slope 250 ft.

61.90 Top of spur, projects S. Desc. abrupt E. slope 450 ft. through dense pinon pine and juniper.

77.37 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 5, 6, 31 and 32, with