

Independent resurvey of the Third Standard Parallel North
through range 50 East.

Chains. Note: Diligent search for old corners was made at a westing of 40.00 and 80.00 chs. from the old standard corner of T. 16 N., Rs. 50 and 51 E., described in the field notes of T. 15 N., R. 51 E., but no old corners were found along this line.

From the standard corner of Ts. 16 N., Rs. 50 and 51 E., which is an iron post, 3 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 15 N., R. 51 E.,

West, on a true line, on the S. Bdy. of sec. 36.

Desc. 20 ft. over rolling land, through very scattering juniper.

2.10 Dry wash, drains NW. Asc. NE. slope 60 ft.

13.70 Point of spur, projects NW. Desc. 20 ft.

16.00 Base of hills bearing N. and S. Leave scattering juniper. Desc. gradual SW. slope 150 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the standard $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} \text{SC} \\ \frac{1}{4} \text{ S36} \\ \hline 1926 \end{array}$$

At base of post deposit a granite stone, 10 x 8 x 8 ins., marked with cross (x). Pits impracticable and no other accessories available.

Desc. gradual SW. slope 50 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the standard cor. of secs. 35 and 36, with brass cap mkd.

$$\begin{array}{r|l} \text{S} & \text{C} \\ \hline \text{T16N} & \text{R50E} \\ \text{S35} & \text{S36} \\ \hline 1926 \end{array}$$

At base of post, deposit a granite stone, 10 x 8 x 4 ins. marked with cross (x). Pits impracticable and no other accessories available.

Land; E. 16.00 chains rolling; W. 64.00 chs. slightly rolling. Undergrowth, white sage; very scant growth of grass. Soil, gravelly and rocky clay of medium texture. Timber, scattering juniper E. 16 chains.