

Subdivision of T. 15 N., R. 51 E.

Chains

N 0°03' W, on true line bet. secs. 4 and 5.


Over mountainous land, through scattering timber and scant undergrowth, asc. 670 ft. along a SW slope to,

25.00 Spur, projects NW, desc. 445 ft. along a NW slope to

40.00 On a NW slope,

Set an iron post, 3 ft. long and 1 in. in dia. 28 ins.

in the ground for the $\frac{1}{4}$ sec. cor., with a brass cap marked:



From which,,

A mahogany, 6 ins. in dia. bears N 4°00' E, 105

lks. dist., marked: $\frac{1}{4}$ S5BT.

A pinon, 3 ins. in dia. bears N 43°00' W, 15 lks.


dist., marked: 'BT'

Continue desc. of 50 ft. along a NW slope on the W slope of the spur.

75.30 Spur, projects NW, desc. 175 ft. over a N slope to

82.13 Intersect the Third Standard Parallel North at a point 3.34 chains East of the standard corner of secs. 32 and 33, heretofore described and at the point of intersection,

Set an iron post, 3 ft. long and 2 ins. in dia. 28 ins. in the ground for the closing corner of secs. 5 and 4, with a brass cap marked:



From which,

A mahogany, 4 ins. in dia. bears S 37°15' E, 51

lks. dist., marked: T15NR51ES4CGBT.

A mahogany, 5 ins. in dia. bears S 15°45' W, 98

lks. dist., marked: T15NR51ES5BT.