

Subdivision of T. 15 N., R. 51 E.

Chains

47.60	Draw, drains N, asc. 220 ft. along a W slope to,
56.40	Spur, projects N 5° W, desc. 20 ft. along a broken N slope to.
77.99	The cor. of secs. 5, 6, 7 and 8.
	Land, rough mountain slopes, general N exposure and drainage.
	Soil, gravelly to rocky clay loam, 3rd rate.
	Timber, pinon and juniper.
	Undergrowth, sagebrush and buckbrush.
	Fair grazing.
	N 0°03' W, on true line bet. secs. 5 and 6,
	Over mountainous land, through scattering timber and scant undergrowth, desc. 350 ft. along a NE slope to,
18.00	Nine Mile canyon, (dry), drains NW, asc. 120 ft. over a broken SW slope to,
40.00	On a broken SW slope,
	Set an iron post, 3 ft. long and 1 in. in dia. 26 ins. in the ground to solid rock and in a mound of stone for the $\frac{1}{4}$ sec. cor., with a brass cap marked:
	$\begin{array}{c} \frac{1}{4} \\ \\ S6 \quad \quad S5 \\ 1925 \end{array}$
	From which,
	A mahogany, 5 ins. in dia. bears S 49°00' E, 87 lks. dist., marked: $\frac{1}{4}$ S5BT.
	A pinon, 8 ins. in dia. bears S 81°00' W, 32 lks. dist., marked: $\frac{1}{4}$ S6BT.
	Asc. 15 ft. along a SW slope to,
43.00	Spur, projects W, desc. 165 ft. along a NW slope to,
54.00	Draw, drains W, asc. 240 ft. along a SW slope to,
68.00	Spur, projects W, desc. 75 ft. along a NW slope to,
73.00	Draw, drains W, asc. 95 ft. along a S slope to,
82.22	Intersect the Third Standard Parallel North, at a point 3.24 chains east of the standard cor. of secs. 31 and