

Dependent Resurvey of the E. Bdy. of T. 33 N., R. 18 E.

Chains.

From the original cor. of secs. 19, 24, 25 and 30, hereinafter described,

N. $0^{\circ} 02' W.$ on retracement, setting temporary points at 40.00 and 80.00 chs. and making diligent search for old corners. None were found until a point,

319.48 Fall 102 lks. E. of the cor. of Ts. 33 and 34 N., R. 18 E., which is the original corner of Ts. 33 and 34 N., Rs. 18 and 19 E., hereinafter described.

The course of this line is N. $0^{\circ} 13' W.$ and the proportionate length of each mile is 79.87 chs.

I remonument the original corner of Ts. 32 and 33 N., Rs. 18 and 19 E., which is a granite stone, 8 x 10 x 12 ins. marked dimly with 6 grooves on N. and W. faces, and set in an old mound of stone, by raising a large mound of stone around the corner.

From the original corner of Ts. 32 and 33 N., Rs. 18 and 19 E., N. $0^{\circ} 34' E.$ on a true line, on the E. Bdy. of sec. 36.

Desc. NE. slope 30 ft. over rolling mountainous land.

6.30 Small stream of running water, 2 lks. wide, 2 ins. deep from spring heading 1.00 ch. W. of line. Asc. 190 ft.

18.20 Top of spur, projects S. $60^{\circ} E.$ Desc. 30 ft.

34.20 Dry wash, drains S. $20^{\circ} E.$ Asc. broken and rocky SE. slope 160 ft.

40.40 Top of cliff 50 ft. high, facing SW.

40.51 $\frac{1}{2}$ The proportionate point. Set an iron post 3 ft. long, 1 in. in diam., 14 ins. in the ground, to solid rock, in a mound of stone, 4 ft. base, 20 ins. high, for the $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap mkd.

$\frac{1}{4}$
836
1927

At base of post deposit a granite stone 10 x 7 x 5 ins., marked with cross (x).