

INDEPENDENT RESURVEY OF THE WEST BOUNDARY OF T. 16 N., R. 51 E.

Chains

From point of intersection the cor. of Tps. 17 N., Rs. 50 and 51 E., bears West, 8.19 chs. dist.

Land, gently rolling.

Soil, 27 ins. sandy clay loam; 1st and 2nd rate.

Timber, none.

Undergrowth, sagebrush, shadscale, white sage, rabbit brush.

General drainage, W.

Grazing, poor.

SUBDIVISION OF T. 16 N., R. 51 E.

From the standard cor. of secs. 35 and 36, on S. bdy. of township, an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

N. 0°01' W., bet. secs. 35 and 36.

Over mountainous land, through heavy timber and scattering undergrowth.

- 1.80 Spur, projects N. 80° E.; desc. NW. slope 20 ft.
 4.90 Draw, drains N. 80° E.; asc. stony SE. slope 10 ft.
 7.80 Spur, projects N. 85° E.; desc. stony NW. slope 20 ft.
 10.15 Ravine, drains N. 75° E.; asc. stony SE. slope 25 ft.
 19.90 Spur, projects N. 60° E.; desc. stony NW. slope 55 ft.
 26.55 Ravine, drains N. 80° E.; asc. stony SE. slope 25 ft.
 30.25 Spur, projects N. 85° E.; desc. stony N. slope 30 ft.
 31.10 Draw, drains E.; asc. stony SE. slope 30 ft.
 37.70 Spur, projects E.; desc. NE. slope 10 ft. to 42.90 chs.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a granite stone, 3x2x1 ins., mkd. X, deposited at the base, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S35 | S36
 1933

from which,

A knarred pinon, 8 ins. diam., bears N. 71-3/4° W.
 18 lks. dist., mkd. BT only.

A knarred juniper, 10 ins. diam., bears S. 5-3/4° E.,
 18 lks. dist., mkd. $\frac{1}{4}$ S36BT.

- 42.90 Spur, projects N. 75° E.; desc. stony NW. slope 25 ft.
 46.60 Ravine, drains N. 75° E.; asc. stony SE. slope 10 ft.
 49.70 Spur, projects N. 75° E.; desc. stony NW. slope 25 ft.
 53.30 Draw, drains E.; asc. stony SE. slope 25 ft.