

INDEPENDENT RESURVEY OF THE SUBDIVISION OF T. 13 S., R. 70 E.

Chains
40.00Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \hline S4 \quad | \quad S3 \end{array}$$

1934

raise a mound of stone, 2 ft. base, to top of post.

Asc. 40 ft. over S. slope.

41.60

Spur, projects W.

50.80

Spur, projects N. 85° W.

53.60

Wash, drains W. 80° W.; asc. 25 ft.

61.00

Spur, projects N. 70° W.

67.20

Wash, drains N. 75° W.; asc. 37 ft.

71.00

Spur, projects N. 70° W.

80.00

Set an iron post, 3 ft. long, 1 in. diam., 25 ins. in the ground over a cross (X) cut in solid rock, for the cor. of lots 8 and 9 of sec. 3, and lots 5 and 12 of sec. 4, with brass cap mkd.

T13SR70E

$$\begin{array}{c} 5 \quad | \quad 8 \\ \hline S4 \quad | \quad S3 \\ \hline 12 \quad | \quad 9 \end{array}$$

1934

raise a mound of stone, 3 ft. base, to top of post.

82.60

Wash, drains N. 70° W.; desc. 65 ft.

84.00

Spur, projects NW.

98.42

Intersect the third standard parallel south, at a point 7.41 chs. West of the standard cor. of secs. 33 and 34, T. 12 S., R. 70 E., which is an iron post, mkd. and witnessed as described in Book "A", of this group.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground for the closing cor. of secs. 3 and 4, with brass cap mkd.

T12SR70E

S33

$$\begin{array}{c} S4 \quad | \quad S3 \end{array}$$

T13SR70E

CC

1934

Deposit a limestone, 6x5x4 ins., mkd. with a cross (X) at base of the post.