

DEPENDENT RESURVEY OF PORTION OF N. BOUNDARY T. 7 N., R. 46 E.

Chains Desc. NE. slope 195 ft. to
 79.33 The original sec. cor., which is a conglomerate stone,
 5X12X14 ins., mkd with 1 notch on E. and 5 notches on W.
 faces; and old mound of stone N. of cor., alongside
 original cor.

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in
 the ground, for the cor. of secs. 1 and 2, T. 7 N.,
 R. 46 E., with brass cap mkd

T8N R46E

S 34

S2 S1

T7N R46E

1931

From which

A pinon, 10 ins. dia., bears S. $64\frac{1}{2}^{\circ}$ E., 114 lks. dist.,
 mkd T7NR46ES1BT

A juniper, 8 ins. dia., bears S. $40\frac{1}{4}^{\circ}$ W., 59 lks. dist.,
 mkd T7NR46ES2BT

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

Land, mountainous. Soil, sandy, gravelly, 3rd rate.

Timber, pinon, juniper, mt. mahogany.

Undergrowth, sagebrush, bunch grass.

General drainage, NW. Grazing, fair.

S. $89^{\circ} 22'$ E., along N. bdy. sec. 1, T. 7 N., R. 46 E.

Over rough mountainous land through heavy timber

Asc. 30 ft. to

3.25 Westing of 160.00 chs. from the cor. of T. 8 N., Rs. 46
 and 47 E

Set an iron post, 3 ft. long, 2 ins. dia., 10 ins. in the

ground to solid rock, in a large mound of stone, for

the cor. of secs. 34 and 35, T. 8 N., R. 46 E., with

brass cap mkd

T8N R46E

S34 S35

S1

T7N R46E

1931