

DEPENDENT RESURVEY OF A PORTION OF T. 16 N., R. 21 E., M.D.Mer., Nevada

Chains

Dependent Resurvey of Secs. 16, 17, 20 and 21,
in T. 16 N., R. 21 E., M.D.Mer., Nevada as
originally surveyed by R.R.W. Norris, U. S.
Deputy Surveyor under Contract # 2 in 1867.

At the point for cor. of secs. 21, 22, 27 and 28 which is marked by
the original cor. stone --- a basalt rock, 24 x 12 x 6 ins., project-
ing 12 ins. above the surface --- firmly set in the center of an old
embedded mound of stone and marked 3 notches on E. and 2 notches on
S. edges.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to
solid rock, with the original stone deposited at the base, mounded to
top with stone, for cor. of secs. 21, 22, 27 and 28, with brass cap
mkd.

T16NR21E

S 21 S 22

S 28 S 27

1932

Thence

N. 0° 43' E., bet. secs. 21 and 22, (S. half mile)

Over gently rolling land descending gradual N. slope.

5.20 Small draw, drains E.

6.03 Telephone-telegraph line, bears NW. and SE.

6.99 Railroad, bears NW. and SE.

8.60 Road, bears NW. and SE.

11.40 Main draw, drains SE.; continue over gentle rolling S. slope.

26.30 Old stage road (unused) bears N. 60° E. and S. 60° W.

28.85 Telephone line, bears E. and W.

36.40 Road, bears E. and W.

40.14 The point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, which is mkd. by a
basalt rock, 15 x 10 x 4 ins.; faintly marked on W. face and set in
an old embedded mound of stones.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground with
original cor. stone deposited at the base, for $\frac{1}{4}$ sec. cor., with
brass cap mkd.

 $\frac{1}{4}$

S21 S22

1932

raise a mound of
stone, 4 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

N. 0° 06' E., bet. secs. 21 and 22, (N. half mile.)

Continue over gentle S. slope.