

SUBDIVISION OF T. 16 N., R. 49 E.

430

Chains

43.40

Ravine, course S. 20° W.; asc. 125 ft.

54.00

Top of spur, projects S. 20° W.; desc. 220 ft.

68.30

Channel of Whitesage canyon, with a small trickling stream of clear water, 8 ins. wide, $\frac{1}{4}$ ins. deep, course S. 5° E.; asc. 95 ft..

76.00

Top of spur, projects S. 25° E.; desc. 25 ft.

77.47

Intersect the E. bdy. of T. 16 N., R. 48 E.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 30 and 31, with brass cap mkd.

T16N
R48E
S13

T16N
S30
S31
R49E

CC

1939

from which

A pinon pine, 9 ins. diam., bears N. 89° E., 26 lks. dist., mkd. T 16 N R 49 E S 30 C C B T.

A pinon pine, 9 ins. diam., bears S. 64 $\frac{3}{4}$ ° E., 58 lks. dist., mkd. T 16 N R 49 E S 31 C C B T.

Land, mountainous.

Soil, sandy, gravelly and rocky; 4th rate.

Timber, juniper and pinon pine; undergrowth, sagebrush and a fair growth of grass.

From the closing cor. of secs. 30 and 31, on the E. bdy. of T. 16 N., R. 48 E.

South on blank line.

17.59

The cor. of secs. 13 and 24, T. 16 N., R. 48 E., described in the official record of T. 16 N., R. 48 E., under this group.

39.97

Midpoint between the closing cor. of secs. 30 and 31 and the SW. standard closing cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., for sec. 31 only, with brass cap mkd.

$\frac{1}{4}$ S 31

1939

from which

A pinon pine, 4 ins. diam., bears S. 38 $\frac{1}{2}$ ° E., 170 lks. dist., mkd. B T only.

A pinon pine, 6 ins. diam., bears S. 74 $\frac{1}{2}$ ° E., 173 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.

57.59

The $\frac{1}{4}$ sec. cor. for sec. 24, on E. bdy. T. 16 N., R. 48 E., described in book of T. 16 N., R. 48 E., under this group.

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 03' W., bet. secs. 29 and 30.

Over mountainous land, through scattering timber and dense under-