

432

SUBDIVISION OF T. 16 N., R. 49 E.

Chains	
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Desc. 190 ft. over NW. slope.
50.60	Ravine, course S. 80° W. for 6.00 chs., thence S. 60° W.; desc. 30 ft.
53.50	Point of spur, projects S.; desc. 65 ft.
57.90	Ravine, course S.; asc. 150 ft.
66.10	Top of rimrock, and cliff 15 ft. high, bears N. 30° E. and S. 30° W.; asc. 100 ft. over SE. slope.
80.00	The cor. of secs. 19, 20, 29 and 30. Land, mountainous. Soil, sandy, gravelly and rocky; 4th rate. Timber, juniper and pinon pine; undergrowth, sagebrush, and a fair growth of grass.
	West, on true line bet. secs. 19 and 30. Over mountainous land, through scattering timber and dense under- growth, asc. 55 ft. over SE. slope.
8.40	Saddle in spur ridge, ridge, bears N. 50° E. and S. 35° W.; desc. 75 ft. along a NE. slope.
35.00	Top of spur, projects NW.; desc. 90 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, with a limestone, 6x5x3 ins., mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S 19 $\frac{1}{4}$ S 30 1939 raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Desc. 50 ft. over SW. slope.
43.20	To a point from which Sheep Spring, bears S. 51° W. Continue to desc. 320 ft. over SW. slope.
61.10	Ravine, course S. 15° W.; asc. 225 ft. over SE. slope.
77.39	Intersect the E. bdy. of T. 16 N., R. 48 E. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 19 and 30, with brass cap mkd.
	T16N T16N R48E S12 1939 T16N S19 S30 R49E CC ✓ from which
	A pinon pine, 5 ins. diam., bears N. 21° E., 95 lks. dist., mkd. T 16 N R 49 E S 19 C C B T. ✓