

SUBDIVISION OF T. 16 N., R. 49 E.

Chains	
58.30	Leave dense aspen timber, bears N. and S.
59.00	Point of spur, projects N.; desc. 60 ft.
71.00	Head of hillside drain, course N.; asc. 10 ft. Enter dense aspen timber, bears N. and S.
77.00	Top of spur, projects NW.; desc. 120 ft.
80.00	The cor. of secs. 17, 18, 19 and 20.
	Land, mountainous. Soil, light sandy loam, medium texture, moist, mixed with decomposed limestone and lava, much loose rock on surface; 3rd rate. Timber, quaking aspen, juniper, pinon pine and mahogany; Undergrowth, sagebrush, buckbrush and a fair growth of grass.
	West, on true line, bet. secs. 18 and 19.
	Over mountainous land, through dense timber and undergrowth, desc. 5 ft.
0.50	Hillside drain, course NW.; asc. 230 ft. over NE. slope.
3.00	Leave dense aspen timber, bears N. and S.; continue through scattering timber.
20.00	Top of spur, projects N.; desc. 100 ft. along N. slope.
32.00	Top of spur ridge, bears N. 20° W. for 5.00 chs. thence N. 70° W. and S. 15° W.; desc. 40 ft.
37.70	Head of hillside drain, course N. 70° W.; asc. 5 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S 18 $\frac{1}{4}$ S 19 raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, N. of cor.
46.10	Top of spur, projects NW.; desc. 75 ft.
58.80	Wash, course N. 20° W.; asc. 30 ft.
63.70	Point of spur, projects N.; desc. 10 ft. From this point, a small pond, bears S. 15.00 chs. dist.
66.50	Head of drain, course N.; asc. 50 ft.
76.20	Top of spur, projects N.; desc. 10 ft.
77.29	Intersect the E. bdy. of T. 16 N., R. 48 E.
	Set an iron post, 3 ft. long, 2 ins. diam., 4 ins. in the ground to bedrock, with a limestone, 8x6x5 ins., mkd. X, deposited at the base, and in a mound of stone, to top, for closing cor. of secs. 18 and 19, with brass cap mkd.

T16N	T16N
R48E	S18
S1	S19
	R49E
1939	