

438

## SUBDIVISION OF T. 16 N., R. 49 E.

## Chains

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S 7

 $\frac{1}{4}$ 

S 18

1939

raise a mound  
of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

Asc. 315 ft. along an E. slope.

51.00

Enter dense timber, bears N. and S.

58.40

Top of spur, slopes N.; desc. 25 ft.

67.90

Head of wash, course N. 60° W.; asc. 15 ft.

70.00

Point of spur, projects N. 60° W.; desc. 50 ft.

74.90

Head of wash, course N.; asc. 25 ft.

77.19

Intersect the E. bdy. of T. 17 N., R. 48 E.

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, to bedrock, with a limestone, 8x7x6 ins., mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 7 and 18, with brass cap mkd.

T17N

R48E

S36

T16N

S 7

CC

S18

R49E

1939

raise a mound  
of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

From the point of intersection, the cor. of Tps., 16 and 17 N., R. 48 E., bears South, 19.10 chs. dist., described in book of T. 16 N., R. 48 E., under this group.

Land, mountainous.

Soil, sandy, rocky and gravelly; 3rd rate.

Timber, juniper, pinon pine and mahogany; undergrowth, sagebrush and a fair growth of grass.

At midpoint bet. the closing cors. on the W. bdy. of sec. 18,

Set an iron post, 3 ft. long; 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. for sec. 18, with brass cap mkd.

 $\frac{1}{4}$  S 18

1939

raise a mound  
of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

From this  $\frac{1}{4}$  sec. cor., the  $\frac{1}{4}$  sec. cor., for sec. 1 on the E. bdy. of T. 16 N., R. 48 E., bears South 17.70 $\frac{1}{2}$  chs. dist., described in book of T. 16 N., R. 48 E., under this group.

From the cor. of secs. 7, 8, 17 and 18.