

INDEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL
 TOWNSHIP 36 NORTH THROUGH RANGE 30 EAST
 TOWN OF ADAMS, ADAMS COUNTY, MICHIGAN

Chains	
50.00	Wash, course S. 60° W.
63.18	N. 1 lk. from the secant.
	The closing cor. of Ts. 15 N., Rs. 30 and 31 E., a 3 in. iron post, 3 ft. long, firmly set, mkd. and witnessed as described in the field notes of T. 15 N., R. 30 E., executed under this group.
	Continue to desc. 40 ft. over W. slope.
	Diff. bet. meas. of 80.00 chs. by two sets of chainmen is 4 lks.; position of midpoint--
	By 1st set, 80.02 chs.
	By 2nd set, 79.98 chs; the mean of which is
80.00	On the secant,
	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, for standard cor. of secs. 35 and 36, with brass cap mkd.
	SC
	T16N R30E
	S35 S36
	1937
	From this cor. the original standard sec. cor. bears, S. 19° 10' W., 2.11 chs. dist., a volcanic stone 6x8x13 ins. set 6 ins. in the ground, mkd. SC on N., 5 grooves on W. and 1 groove on E. faces, with a mound of stone N. of cor.
	I destroy the original standard sec. cor.
	Land, rolling mountains.
	Soil, rocky, 4th rate.
	No timber; undergrowth, shadscale, greasewood and button sage.
	Grazing, good.
	West, along S. bdy. of sec. 35, on a transit line describing the secant, which bears N. 89° 58.6' W.
	From this point westward the chaining was measured by only one set of chainmen since the Townships to the South were subdivided and closed against the third standard parallel north.
	Over rolling foothills through medium dense undergrowth, asc. 50 ft. along rolling S. slope.
1.60	Wash, course S. 60° W.
20.40	Spur, slopes N. 30° E., desc. 20 ft. over gentle W. slope.
26.80	Slope changes to S., desc. 140 ft. along spur sloping to W.
40.00	S. 1 lk. from the secant,
	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground and in a mound of stone to top, for standard ¼ sec. cor., with brass cap mkd.