

DEPENDENT RESURVEY OF A PORTION OF N. BDY. T. 4 N., R. 66 E.

Chains	West, on a true line bet. secs. 5 and 32, Over rolling land, thru scattering timber and undergrowth.
40.00	The $\frac{1}{4}$ sec. cor. bet. secs. 5 and 32, an iron post, 1 in. diam., 10 ins. above the ground, mkd. and witnessed, as described in the official record, N. 89° 57' W., on true line, bet. secs. 5 and 32. Asc. 20 ft. over rolling land, thru scattering timber and undergrowth.
11.10	Top of ascent, bears N. and S.; over nearly level land.
13.20	Road, bears N. 10° E. to Poney Spring, and S. 10° W.
17.60	Creek, 30 lks. wide, dry, course N. 75° E.
20.60	Creek, same, 30 lks. wide, dry, course S. 80° E.
24.70	Creek, same, 30 lks. wide, dry; course N. 80° E., asc. 70 ft.
25.90	Road, bears N. and S.
40.00	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the cor. of secs. 5, 6, 31 and 32, with brass cap mkd. T5N R66E S31 S32 S6 S5 T4N 1937 raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land, rolling. Soil, rocky clay, 3rd rate. Timber, pine, juniper and cedar; undergrowth, sagebrush, greasewood and native grasses.
SURVEY OF A PORTION OF NORTH BOUNDARY	
T. 4 N., R. 66 E.	
From the cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the Tp., N. 89° 57' W., bet. secs. 6 and 31. Asc. 270 ft. over rolling land, on an E. slope, thru scattering timber and undergrowth.	
28.00	Shallow draw, drains N. 65° E.
35.70	Creek, 30 lks. wide, 3 ins. deep, course NE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, with brass cap mkd. S31 $\frac{1}{4}$ S 6 1937