

Dependent Resurvey of the W. Bdy., T. 5 N., R. 67 E.
with establishment of cors. at regular intervals for T. 5 N., R. 66 E.

Chains

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T6N R66E
S36
S 1 | S 6
R66E R67E
T5N
C C
1957

from which

The standard ¼ sec. cor. of sec. 36, T. 6 N., R. 66 E., an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of the 1st Standard Parallel North through R. 66 E., by H. G. Parker in 1956, bears W., 2 chs. dist.

Land, nearly level.

Soil, sandy.

Timber, S. ¼ scattered juniper, N. ¾ none.

Undergrowth, S. ¼ mixed sage, N. ¾ crested wheat grass.

Dependent Resurvey of the N. Bdy., T. 4 N., R. 66 E.
with establishment of cors. at regular intervals for T. 5 N., R. 66 E.

Restoration of the survey executed by
Monroe and Bateman, Deputy Surveyors, in 1872

The W. 2 miles of this line were resurveyed partly in 1919 by J. C. Clark and partly by Inch and McConkie in 1937.

At the cor. of Ts. 4 N., Rs. 66 and 67 E., which is a cedar stake, set, mkd. and witnessed as described in the official record of the Monroe and Bateman survey, executed in 1872. This cor. was originally established for Ts. 4 and 5 N., Rs. 66 and 67 E.; it now functions as a cor. of Ts. 4 N., Rs. 66 and 67 E. only.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T5N R66E
S36
S 1 | S 6
T4N
R66E R67E
1957

Set a cedar post, 5 ft. long, 4 ins. diam., 24 ins. in the ground, alongside iron post.

from which

A juniper, 4 ins. diam., bears S. 62° 30' E., 51 lks. dist., mkd. T4N R67E S6. BT.

A juniper, 8 ins. diam., bears S. 68° 45' W., 98 lks. dist., mkd. T4N R66E S1. BT.

From this corner, the SE. cor. of T. 5 N., R. 66 E., an iron post, 2½ ins. diam., hereinbefore described, bears N. 89° 48' E., 6.65 chs. dist.