

Independent Resurvey of a Portion of the Subdivision, T. 5 N., R. 66 E.

Chains

Point for the W. 1/16 sec. cor. on the N. bdy. of sec. 6, at 80 chs. westing from the closing cor. of secs. 5 and 6, which point falls on the S. bdy. of sec. 36, T. 6 N.; R. 65 E.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

1/16 T6N R66E  
S 6 80  
T5N  
1957

Set a cedar post, 5 ft. long, 3 ins. diam., 22 ins. in the ground, alongside iron post.

The cor. falls 50 lks. S. of a wash, 10 lks. wide, 2 ft. deep, drains N. 75° E.

from which

A juniper, 8 ins. diam., bears S. 26° 45' E., 100 lks. dist., mkd. 1/16 S6 BT.

The closing cor. of secs. 1 and 6, T. 5 N., Rs. 65 and 66 E., which is monumented with a 3 in. iron post, set, mkd. and witnessed as described in the official record of the survey of the E. bdy. of T. 5 N., R. 65 E., by J. C. Clark in 1919, bears N. 89° 55' W., 7.42 chs. dist.

Survey of Patented Tracts in T. 5 N., R. 66 E.

Tract 37

State Selection, approved list 20, dated May 8, 1897 for the SE¼SE¼ of sec. 4, T. 5 N., R. 66 E.

Note: The field notes of the original survey of the subdivision of this township give angle ties from the cor. of secs. 4, 5, 8 and 9 and from the ¼ sec. cor. of secs. 4 and 9 to "Pony Springs". This results in a calculated tie from "Pony Springs" to the original position of the cor. of secs. 3, 4, 9 and 10, S. 82° 05' E., 53.19 chs. dist.. This original position for the cor. of secs. 3, 4, 9 and 10 is adopted as angle point 4 for Tract 37.

At the point for the cor. of angle point 1, Tract 37, which bears N. 25° 20' E., 37.55 chs. dist. from the ¼ sec. cor. of secs. 5 and 8.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

AP 1 T5N R66E  
Tr 37 S 5  
1957

Thence

West, along the N. bdy. of Tract 37.

Over nearly level land, through sagebrush.

3.00

Fence, 4 strand barbed wire on cedar posts, bears N. 80° E. and S. 80° W.; enter grass land.