

Dependent Resurvey of the East Boundary of T. 13 S., R. 47 E.

Chains	
80.00	The original cor. of secs. 25, 30, 31, and 36, which is mkd. by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record. This cor. now functions for secs. 25 and 36 only. I alter the markings on the brass cap to read T13S R47E S25 S36 57 1921 I repair and enlarge the auxiliary mound of stone. Land, nearly level. Soil, sandy and gravelly loam. Timber, none; undergrowth, creosote bush.
12.64	North, along the E. bdy. of sec. 25. Over gently rolling land, through scattered undergrowth. The closing cor. of sec. 34, T. 13 S., R. 47½ E., and sec. 3, T. 14 S., R. 47 E., which is mkd. by an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the field notes of the independent resurvey of the north bdy. of T. 14 S., R. 47 E., executed concurrently under this same group.
40.00	True point for the original ¼ sec. cor. of secs. 25 and 30 at record dist. south of its witness cor. falls in wash draining SW.
40.40	The original witness ¼ sec. cor. of secs. 25 and 30, which is mkd. by and iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record. This cor. now functions for sec. 25 only. I alter the markings on the brass cap to read T13S R47E S25 WC 57 1921 I repair and enlarge the auxiliary mound of stone.
80.00	The original cor. of secs. 19, 24, 25, and 30, which is mkd. by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record. This cor. now functions for secs. 24 and 25 only. I alter the markings on the brass cap to read T13S R47E S24 S25 57 1921 I repair and enlarge the auxiliary mound of stone. Land, gently rolling. Soil, sandy and gravelly loam. Timber, none; undergrowth, creosote bush.
	North, along the E. bdy. of sec. 24.