

Independent Resurvey of a Portion of the North Bdy., T. 14 S., R. 47 E.

Chains

T13S R47½E
¼ S 35
S 2
T14S R47E
1957

Continue over heavily rolling land; asc. 10 ft. over SE. slope.

41.00 Top of ascent, slopes S.; desc. 110 ft. over WSW. slope.

52.00 Wash, 20 lks. wide, 4 ft. deep, drains SW.

67.70 Wash, 1 ch. wide, 8 ft. deep, drains SW.; asc. 29 ft. over SE. slope.

71.00 Top of ascent, slopes S.

72.80 Wash, 30 lks. wide, 15 ft. deep, drains SW.

80.00 Point for the cor. of secs. 2, 3, 34 and 35.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T13S R47½E
S 34 S 35
S 3 S 2
T14S R47E
1957

Land, rough mountainous to heavily rolling.

Soil, sandy, gravelly, and rocky.

No timber; undergrowth, sparse creosote bush and shadscale.

West, between secs. 3 and 34.

Over gently rolling land, through scattered undergrowth.

Desc. 209 ft. over WSW. slope.

3.10 Wash, 40 lks. wide, 5 ft. deep, drains SW.

40.00 Point for the ¼ sec. cor. of secs. 3 and 34.

Set an iron post, 36 ins. long, 1 in. diam., 6 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T13S R47½E
¼ S 34
S 3
T14S R47E
1957

Continue over gently rolling land; desc. 86 ft. over W. slope.

59.42 Intersect the east bdy. of T. 13 S., R. 47 E.

Point for the closing cor. of secs. 34, T. 13 S., R. 47½ E., and sec. 3, T. 14 S., R. 47 E.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.