

Dependent Resurvey, Subdivision, T. 25 N., R. 41 E.

Chains	
	From the cor. of secs. 1, 2, 11 and 12. N. 85° 22' W., bet. secs. 2 and 11. Over nearly level land, through sagebrush and shadscale. 40.45 Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T25N R41E S 2 ¼ S11 1959
53.40	Secondary road, bears N. 30° W. and S. 30° E.
67.00	Secondary road, bears N. 30° W. and S. 20° E.
74.00	Dry wash, 4 ft. deep, 30 lks. wide, drains S. 10° E.
80.90	The cor. of secs. 2, 3, 10 and 11. Land, nearly level. Soil, loam. Vegetation, sagebrush and shadscale.
	N. 0° 01' E., bet. secs. 2 and 3. Over nearly level land, through sagebrush and shadscale.
20.80	Primary access road, bears N. 45° E. and S. 45° W.
39.82	The ¼ sec. cor. of secs. 2 and 3, mkd. by a stone, 10x8x4 ins., firmly set, with ¼ grooved on the W. face. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T25N R41E S 3 ¼ S 2 1959 Bury old cor. stone alongside iron post.
17.80	North, beginning new measurement. Intersect the Fifth Standard Parallel North. Point for the closing cor. of secs. 2 and 3. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.