Chains	
	Over nearly level land, through scattering undergrowth.
40.10	The cor. of Tps. 7 and 8 S., Rs. 44 and 45 E. Land, nearly level. Soil, light gravel, sandy loam. Timber, none; Undergrowth, sagebrush and creosote bush.

Dependent Resurvey, Portion of the West Boundary, T. 8 S. R. 44 E.

The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp. is monumented with a basalt stone, 15x12x7 ins., above ground, firmly set, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T8S
R43E R44E
S12 | S 7
S13 | S18
1961

Bury the original cornerstone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

N. 0°02'W., bet. secs. 7 and 12.

Over nearly level land through scattering undergrowth.

10.80 Bladed road, bears E. and W.

40.17 The ¼ sec. cor. of secs. 7 and 12, monumented with a basalt stone, 16x12x10 ins., above ground, firmly set, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T8S
R43E R44E
¼
S12 | S7
1961

Bury the original cornerstone alongside the iron post.

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.

N. 0°01'W., beginning new measurement.

Over nearly level land through scattering undergrowth.

40.17 The cor. of secs. 1, 6, 7 and 12, monumented with a basalt stone, 12x12x10 ins., above ground, firmly set, marked and witnessed as described in the official record.

At the corner point