

CHAINS	
80.67	The cor. of secs. 29, 30, 31 and 32. Land, gently rolling. Soil, sandy clay. Undergrowth, sagebrush, shadscale and greasewood.
	N. 88° 27' W., bet. secs. 30 and 31. Over gently rolling land, through medium undergrowth. 4.10 Telephone line, bears S. 20° E. and N. 20° W. 4.50 Gravel road, bears S. 20° E. and N. 20° W. 40.27 Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd. T43N R32E $\frac{1}{4}$ S 30 S 31 1962
49.10	Graded road, bears N. and S.
49.40	Graded road, bears N. 15° E. and S. 15° W.
61.80	R.E.A. powerline, bears NE. and SW.
68.70	Trail road, bears N. 30° E. and S. 30° W.
72.90	Fence, 5 strand barb-wire, bears N. and S.
79.14	The cor. of secs. 25, 30, 31 and 36, on the W. bdy., monumented with an iron post, 2½ ins. diam., set, mkd., witnessed as described in the field notes of the concurrent resurvey of T. 43 N., R. 31 E. Land, gently rolling. Soil, sandy clay. Undergrowth, sagebrush, shadscale and greasewood.
	From the cor. of secs. 29, 30, 31 and 32. N. 0° 42' E., bet. secs. 29 and 30. Over nearly level land, through medium undergrowth. 9.20 Graded road, bears E. and W. 21.00 Fence, 4 strand barb-wire, bears NW. and SE. 39.915 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd. T43N R32E $\frac{1}{4}$ S 30 S 29 1962
49.40	Fence, 5 strand barb-wire, bears N. 40° E. and S. 40° W; enter heavy willows.