

Dependent Resurvey E. Bdy. T. 3 S., R. 35 E.

Chains

40.40

The cor. of secs. 1, 6, 7 and 12, which is monumented with a lava stone 20 x 12 x 10 ins. above ground, mkd. with 5 grooves on S. and 1 groove on N. side.
This cor. now refers to secs. 1 and 12, only.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., over a drill hole in bedrock, with brass cap mkd.

T3S
S 1
S 12
R35E
1953

Raise a supporting mound of stone, 5 ft. base, around post to top, with mkd. stone buried in the mound.

Land, gentle, gradual SW. slope.
Soil, alkaline clay loam, covered with lava rock, 2d and 3d rate.
Undergrowth, very light sagebrush and desert growth.
No timber.

N. 0° 15' W., along the E. bdy. of sec. 1. (S½ mile.)

Along gradual W. slope, strewn with lava rock and boulders, thru very light undergrowth.

12.70

Wash, 20 lks. wide, 5 ft. deep, course winding W.

33.40

Wash, 20 lks. wide, 7 ft. deep, course winding W.

40.30

The ¼ sec. cor. of secs. 1 and 6, which is monumented with a black lava stone, 14 x 14 x 6 ins. above ground, mkd. ¼ on W. side. This cor. now refers to sec. 1, only.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

¼
S 1
1953

Bury the mkd. stone along W. side and raise a flat mound of stone, 3 ft. base, around post to top.

N. 0° 04' W., along the E. bdy. of sec. 1. (N½ mile.)

17.00

Wash, 1 ch. wide, 3 ft. deep, course winding W.

40.26

The cor. of Ts. 2 and 3 S., Rs. 35 and 36 E., which is monumented with a black lava stone, 14 x 14 x 12 ins. above ground, mkd. with 6 grooves on N., S. and W. sides.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.