

Dependent Resurvey, Subdivision of T. 3 S., R. 35 E.

Chains

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T3S R35E
S 5 | S 4
S 8 | S 9

1953

Bury the mkd. stone alongside and raise a flat mound of stone, 3 ft. base, around post to top.

From this corner

A wind generator on steel tower on ranch house about 45 chs. dist., bears N. $59\frac{3}{4}^\circ$ E.

A schoolhouse, about 1 mile distant, bears N. $72\frac{3}{4}^\circ$ E.

Land, nearly level, drains easterly.
Soil, alkaline clay loam and sand, boulder strewn, 2d and 3d rate.
Undergrowth, sagebrush and desert growth.
No timber.

N. $0^\circ 21'$ W., bet. secs. 4 and 5. ($S\frac{1}{2}$ mile.)

Descend 40 ft. on gradual NE. slope, thru low brush.

8.40

Unimproved road, in fair condition, bears E. and W.

40.36

The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, which is monumented with a granite stone, 15 x 10 x 6 ins. above ground, mkd. $\frac{1}{4}$ on W. side.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, to bedrock, with brass cap mkd.

$\frac{1}{4}$
S 5 | S 4

1953

Bury the mkd. stone alongside and raise a flat mound of stone, 4 ft. base, around post to top.

N. $0^\circ 33'$ W., bet. secs. 4 and 5. ($N\frac{1}{2}$ mile.)

40.34

The cor. of secs. 4, 5, 32 and 33, on N. bdy. of Tp.

Land, nearly level, drains NE.
Soil, sandy, alkaline clay loam and boulders, 2d to 4th rate.
Undergrowth, sagebrush and desert growth.
No timber.

GENERAL DESCRIPTION

The land in the resurveyed portion of this township is nearly level, in Fish Lake Valley. The mean elevation of the valley floor is 4825 ft. above sea level.

Most of the soil is alkaline clay loam, sandy, about 2d rate, occasionally strewn with boulders which have apparently come from the high mountains to the west of the valley.