

439

Dependent Resurvey, Portion of the East Boundary, T. 19 N., R. 64 E.

Chains

Reestablishment of the Survey Executed by Monroe and Bateman,
Deputy Surveyors, in 1872.

Note: Although the following line was originally surveyed as a common boundary for sections of both adjoining townships, in the present work all corners to the north from the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, are herein reestablished as corners for sections of T. 19 N., R. 64 E. only.

Beginning at the original cor. of secs. 25, 30, 31 and 36, on the E. bdy. of T. 19 N., R. 64 E., which is monumented with a limestone, 8x10x16 ins., firmly set in an old mound of stone, marks weathered off.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 7 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

T19N
R64E R65E
S25 | S30
S36 | S31
1943

from which

A pinon, 14 ins. diam., bears N. $38\frac{1}{4}^{\circ}$ E., 96 lks. dist., mkd. T19N R65E S30 BT.

A juniper, 8 ins. diam., bears S. 75° E., 84 lks. dist., mkd. T19N R65E S31 BT.

A pinon, 8 ins. diam., bears S. 71° W., 24 lks. dist., mkd. T19N R64E S36 BT.

A pinon, 8 ins. diam., bears N. 25° W., 33 lks. dist., mkd. T19N R64E S25 BT.

N. 0° 30' E., bet. secs. 25 and 30.

Over rolling to broken mountainous land, through rather scattering timber and low undergrowth; desc. 70 ft. along spur, slopes N.

6.00 Spur, from S., turns to NE.; desc. 480 ft. over general NW. slope.

39.95 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 25 | S 30
1943

from which

A juniper, 7 ins. diam., bears S. 47° E., 57 lks. dist., mkd. $\frac{1}{4}$ S30 BT.

A juniper, 5 ins. diam., bears S. 42° W., 88 lks. dist., mkd. $\frac{1}{4}$ S25 BT.

Desc. 100 ft. over steep N. slope.