

Subdivision of Fractional T. 15 N., R. 21 E.

Chains	
4.90	Ravine, course N. 40° E.; descend 30 ft. along E. slope.
7.30	Ravine, course N. 70° E.
	Ascend 60 ft. over E. slope.
16.00	Shoulder of spur, slopes E.
27.80	Short side ravine, course E.; along E. slope.
32.60	Spur, projects E.; descend 125 ft. over NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2. Set an iron post, 30 ins. long, 2 ins. diam., 27 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. diam., with brass cap mkd. $\frac{1}{4}$ S 2 S 1 1953 from which A juniper, 4 ins. diam., bears S. $34\frac{1}{4}$ ° E., 116 lks. dist., mkd. $\frac{1}{4}$ S1 BT. A pinon, 6 ins. diam., bears S. $78\frac{1}{4}$ ° W., 58 lks. dist., mkd. $\frac{1}{4}$ S2 BT. Descend 200 ft.
41.25	Very old road, passable, bears E. and W.
53.80	Head of ravine, course NE.
60.00	Spur, slopes N. 15° E.; descend 125 ft.
73.50	Ravine, course N. 25° E.
77.00	Ascend 30 ft.
77.62	Intersect S. bdy. of sec. 36, T. 16 N., R. 21 E., at a point from which the ^{standard} cor. of secs. 35 and 36 bears S. 89° 46' W., 2.57 chs. dist. Point for the closing sec. cor. of secs. 1 and 2. Set an iron post, 30 ins. long, 2 ins. diam., 8 ins. in the ground over a cross (X) mkd. on bedrock, and in a mound of stone, $4\frac{1}{2}$ ft. diam., with brass cap mkd. $\frac{1}{4}$ T16N R21E S36 S 2 S 1 C C T15N R21E 1953 from which A pinon, 6 ins. diam., bears S. 47° E., 80 lks. dist., mkd. T15N R21E S1 CC BT. A juniper, 4 ins. diam., bears S. $24\frac{1}{4}$ ° W., 175 lks. dist., mkd. CC BT.