

Dependent Resurvey, S. Bdy., T. 17 N., R. 20 E.

Chains
39.76

Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T17N	R20E
S 35	S 36
S 2	S 1
T16N	
1947	

from which

A pinon pine, 10 ins. diam., bears N. 11° 15' W., 45 lks. dist., mkd. T17N R20E S35 BT.

Raise a mound of stone, 4 ft. base, 3 ft. high, W. of corner.

From this corner, Cor. No. 3 Sur. No. 275, Lot No. 37 Norrie Mine, which is an iron pipe, 4 ins. diam., 48 ins. above ground, firmly set, marked No. 3 NORRIE, bears N. 50° 20' E., 50.57 chs. dist.

From the same corner, a tall flagpole, triangulation station WAKEFIELD on summit of high mountain, bears N. 20° 35' E., 32.54 chs. dist.

Land, mountainous.

Soil, rocky and gravelly, 4th rate.

Timber, scattering pinon pine; undergrowth, sagebrush.

S. 89° 34' E., bet. secs. 1 and 36.

Over mountainous land. Ascend 400 ft. over general W. slope.

7.00 Small ravine, course S. 80° W.

14.70 Old mining road, bears NE. to Norrie mine and SW. to Jumbo and Virginia City.

20.80 Ridge divide, bears NE. and S.; descend 220 ft. over SE. slope.

32.70 Ravine, course SE.; ascend 120 ft. over SW. slope.

39.76 The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, marked by the original monument, a trap rock, 11 x 8 x 18 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on S. face.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

S 36
$\frac{1}{4}$
S 1
1947

from which

A pinon pine, 12 ins. diam., bears N. 65° E., 200 lks. dist., mkd. $\frac{1}{4}$ S36 BT.