

DEPENDENT RESURVEY, E. BDY., T. 17 S., R. 50 E.

CHAINS

Re-establishment of the survey executed by
E. A. Carter, Deputy Surveyor, in 1881.

The cor. of Tps. 17 and 18 S., Rs. 50 and 51 E., monumented with a limestone rock, 16x12x10 ins., firmly set in the ground, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T 17 S	
R50E	R51E
<u>S 36</u>	<u>S 31</u>
S 1	S 6
T 18 S	
1963	

reset the original cornerstone alongside the iron post.

N. $2^{\circ} 16'$ W., bet. secs. 31 and 36.

Over rough mountainous land; through scattering undergrowth; asc. 200 ft. over rock WSW. slope.

18.00 Top of ridge, bears NNW. and SSE.; desc. 250 ft. over NNE. slope.

38.89 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S	
R50E	R51E
$\frac{1}{4}$	
<u>S 36</u>	<u>S 31</u>
1963	

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Continue over gently rolling land; through scattering undergrowth.

50.00 Road, graded, bears SW. to Ash Meadows, and NE. to Highway No. 93.

77.78 Point for the cor. of secs. 25, 30, 31, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S	
R50E	R51E
<u>S 25</u>	<u>S 30</u>
<u>S 36</u>	<u>S 31</u>
1963	

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.