

DEPENDENT RESURVEY, E. BDY., T. 17 S., R. 50 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S
R50E R51E
 $\frac{S}{S} \frac{12}{13} | \frac{S}{S} \frac{7}{18}$
1963

raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, none; undergrowth, shadscale and creosote bush.

N. $2^{\circ} 16'$ W., bet. secs. 7 and 12.

Over nearly level land, through scattering undergrowth; desc. 50 ft. over gradual NNW. slope.

38.89 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S
R50E R51E
 $\frac{1}{4}$
 $\frac{S}{S} \frac{12}{12} | \frac{S}{S} \frac{7}{7}$
1963

deposit broken glass around the iron post, 6 ins. below the surface of the ground.

48.50 Wash, 20 lks. wide, 1 ft. deep, drains WNW.

55.50 Wash, 50 lks. wide, 1 ft. deep, drains WSW.

77.78 Point for the cor. of secs. 1, 6, 7, and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S
R50E R51E
 $\frac{S}{S} \frac{1}{12} | \frac{S}{S} \frac{6}{7}$
1963

raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, none; undergrowth, shadscale and creosote bush.

N. $2^{\circ} 16'$ W., bet. secs. 1 and 6.

Over slightly rolling land, through scattering undergrowth; asc. 50 ft. over gradual ESE. slope.