

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 17 S., R. 50 E.

CHAINS	
61.00	Road, graded, bears N. 60° E., and S. 60° W.
73.79	Intersect the Fourth Standard Parallel South.
	Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T16S R50E S 36 S 2 S 1 T17S R50E CC 1963
	raise a mound of stone, 3½ ft. base, 2 ft. high, S. of cor.
	From this corner, the standard cor. of secs. 35 and 36, T. 16 S., R. 50 E., hereinbefore described, bears S. 89° 46' W., 12.44 chs. dist.
	Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, none; undergrowth, sagebrush and creosote bush.
	The point for the N. ¼ sec. cor. of sec. 1 is at midpoint and on the N. bdy. of the Tp.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T16S R50E ¼ S 1 T17S R50E 1963
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this corner, the standard ¼ sec. cor. of sec. 36, T. 16 S., R. 50 E., hereinbefore described, bears S. 89° 46' W., 12.39 chs. dist.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.
	N. 1° 02' E., bet. secs. 34 and 35.
	Over gently rolling land, through scattering undergrowth.
40.12	Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.